

Manufacturer:

Epoxy Technology

Product Name:

Epo-Tek® ET353ND Heat Cure Epoxy (8oz)

Manufacturer Part Number:

ET353ND-8OZ

Click here for more details on the Epo-Tek® ET353ND Heat Cure Epoxy (8oz)



Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations Issue date: 2/15/2022 Version: 1.0

SECTION 1: Identification

1.1. Identification

Product form : Mixture

Product name : EPO-TEK® 353ND PART B

1.2. Recommended use and restrictions on use

Use of the substance/mixture : adhesives Recommended use : adhesives

Restrictions on use : Not to be used for any purpose other than the one the product was designed for

1.3. Supplier

Epoxy Technology, Inc. 14 Fortune Drive Billerica, MA, 01821 USA T 978-667-3805 www.epotek.com

1.4. Emergency telephone number

Emergency number : ChemTel: +1 (800) 255-3924, +1 (813) 248-0585

SECTION 2: Hazard(s) identification

2.1. Classification of the substance or mixture

GHS US classification

Acute toxicity (oral) Category 4 H302 Harmful if swallowed

Skin corrosion/irritation Category 1B H314 Causes severe skin burns and eye damage Serious eye damage/eye irritation Category 1 H318 Causes serious eye damage Skin sensitization, Category 1 H317 May cause an allergic skin reaction Carcinogenicity Category 2 H351 Suspected of causing cancer May damage fertility or the unborn child Reproductive toxicity Category 1B

Full text of H statements : see section 16

2.2. GHS Label elements, including precautionary statements

GHS US labeling

Hazard pictograms (GHS US)





Signal word (GHS US) Hazard statements (GHS US) Danger

H314 - Causes severe skin burns and eye damage

H317 - May cause an allergic skin reaction H318 - Causes serious eye damage H351 - Suspected of causing cancel

H360 - May damage fertility or the unborn child Precautionary statements (GHS US) : P201 - Obtain special instructions before use.

P202 - Do not handle until all safety precautions have been read and understood.

P260 - Do not breathe dust/fume/gas/mist/vapors/spray.

2/15/2022 (Issue date) EN (English US) 1/13







Manufacturer: Epoxy Technology

Product Name:

Epo-Tek® ET353ND Heat Cure Epoxy (8oz)

Manufacturer Part Number:

ET353ND-8OZ

Click here for more details on the Epo-Tek® ET353ND Heat Cure Epoxy (8oz)

EPO-TEK® 353ND PART B

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

P261 - Avoid breathing dust/fume/gas/mist/vapors/spray.

P264 - Wash hands, forearms and face thoroughly after handling.

P270 - Do not eat, drink or smoke when using this product.

P272 - Contaminated work clothing must not be allowed out of the workplace.
P280 - Wear protective gloves/protective clothing/eye protection/face protection.

P301+P312 - If swallowed: Call a poison center or doctor if you feel unwell.

P301+P330+P331 - If swallowed: rinse mouth. Do NOT induce vomiting.

P302+P352 - If on skin: Wash with plenty of water.

P303+P361+P353 - If on skin (or hair): Take off immediately all contaminated clothing. Rinse skip with water/shower.

P304+P340 - If inhaled: Remove person to fresh air and keep comfortable for breathing.

P305+P351+P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P308+P313 - If exposed or concerned: Get medical advice/attention.

P310 - Immediately call a poison center or doctor.

P321 - Specific treatment (see supplemental first aid instruction on this label).

P330 - Rinse mouth.

P333+P313 - If skin irritation or rash occurs: Get medical advice/attention

P363 - Wash contaminated clothing before reuse.

P405 - Store locked up.

P501 - Dispose of contents/container to hazardous or special waste collection point, in accordance with local, regional, national and/or international regulation.

2.3. Other hazards which do not result in classification

Other hazards which do not result in classification : Harmful dust may be released during cutting, milling or grinding process.

2.4. Unknown acute toxicity (GHS US)

Not applicable

SECTION 3: Composition/Information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

Name	Product identifier	%	GHS US classification
Substituted imidazole*	CAS-No.: Trade Secret	30 – 60	Acute Tox. 4 (Oral), H302 Skin Irrit. 2, H315 Eye Dam. 1, H318 Skin Sens. 1B, H317
lmidazole	CAS-No.: 288-32-4	≥ 30	Acute Tox. 4 (Oral), H302 Skin Corr. 1C, H314 Eye Dam. 1, H318 Repr. 1B, H360
Substituted imidazole*	CAS-No.: Trade Secret	5 – 10	Acute Tox. 4 (Oral), H302 Acute Tox. 3 (Dermal), H311 Skin Corr. 1B, H314 Eye Dam. 1, H318 Carc. 2, H351

2/15/2022 (Issue date)

Data is subject to change without notice.

EN (English US) 2/13



Contact the professionals at Fiber Optic Center for a quote or to get more details.



Manufacturer:

Epoxy Technology

Product Name:

Epo-Tek® ET353ND Heat Cure Epoxy (8oz)

Manufacturer Part Number:

ET353ND-8OZ

Click here for more details on the Epo-Tek® ET353ND Heat Cure Epoxy (8oz)

EPO-TEK® 353ND PART B

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Name	Product identifier	%	GHS US classification
Substituted imidazole*	CAS-No.: Trade Secret	< 5	Acute Tox. 3 (Oral), H301 Skin Irrit. 2, H315 Eye Dam. 1, H318 STOT SE 3, H335
Substituted anhydride*	CAS-No.: Trade Secret	< 5	Acute Tox. 4 (Oral), H302 Acute Tox. 4 (Dermal), H312 Skin Corr. 1B, H314

^{*}Chemical name, CAS number and/or exact concentration have been withheld as a trade secret

Full text of hazard classes and H-statements : see section 16

SECTION 4: First-aid measures

4.1. Description of first aid measures

First-aid measures general : Call a physician immediately.

First-aid measures after inhalation : Remove person to fresh air and keep comfortable for breathing

First-aid measures after skin contact : Rinse skin with water/shower. Remove/Take off immediately all contaminated clothing. Call a physician immediately.

First-aid measures after eye contact : Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Call a physician immediately.

First-aid measures after ingestion : Rinse mouth. Do not induce vomiting. Call a physician immediately.

4.2. Most important symptoms and effects (acute and delayed)

Symptoms/effects after skin contact : Burns. May cause an allergic skin reaction.

Symptoms/effects after eye contact : Serious damage to eyes.

Symptoms/effects after ingestion : Bu

4.3. Immediate medical attention and special treatment, if necessary

Treat symptomatically.

SECTION 5: Fire-fighting measures

5.1. Suitable (and unsuitable) extinguishing media

Suitable extinguishing media : Water spray. Dry powder. Foam. Carbon dioxide

5.2. Specific hazards arising from the chemical

Hazardous decomposition products in case of fire : Toxic fumes may be released.

5.3. Special protective equipment and precautions for fire-fighters

Protection during firefighting : Do not attempt to take action without suitable protective equipment. Self-contained breathing apparatus. Complete protective clothing.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

6.1.1. For non-emergency personnel

Emergency procedures : Only qualified personnel equipped with suitable protective equipment may intervene. Do not breathe dust/fume/gas/mist/vapors/spray.

Data is subject to change without notice.

Contact the professionals at Fiber Optic Center for a quote or to get more details.



Comments : Components not listed are either non-hazardous or are below reportable limits.



Manufacturer: Epoxy Technology

Product Name:

Epo-Tek® ET353ND Heat Cure Epoxy (8oz)

Manufacturer Part Number:

ET353ND-8OZ

Click here for more details on the Epo-Tek® ET353ND Heat Cure Epoxy (8oz)

EPO-TEK® 353ND PART B

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

6.1.2. For emergency responders

Protective equipment : Do not attempt to take action without suitable protective equipment. For further information refer to section 8: "Exposure controls/personal protection".

6.2. Environmental precautions

Avoid release to the environment. Notify authorities if product enters sewers or public waters.

6.3. Methods and material for containment and cleaning up

Methods for cleaning up : Take up liquid spill into absorbent material. Notify authorities if product enters sewers or public

waters

Other information : Dispose of materials or solid residues at an authorized site.

6.4. Reference to other sections

For further information refer to section 13.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Precautions for safe handling : Ensure good ventilation of the work station. Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Wear personal protective equipment.

Avoid contact with skin and eyes. Do not breathe dust/fume/gas/mist/vapors/spray.

Hygiene measures : Separate working clothes from town clothes. Launder separately. Wash contaminated clothing before reuse. Contaminated work clothing should not be allowed out of the workplace. Do not

eat, drink or smoke when using this product. Always wash hands after handling the product.

7.2. Conditions for safe storage, including any incompatibilities

Storage conditions : Store locked up. Store in a well-ventilated place. Keep cool.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

EPO-TEK® 353ND PART B

No additional information available

Substituted imidazole

No additional information available

Imidazole (288-32-4)

No additional information available

Substituted anhydride

No additional information available

Substituted imidazole

No additional information available

Substituted imidazole

No additional information available

2/15/2022 (Issue date) EN (English US) 4/13







Manufacturer:

Epoxy Technology

Product Name:

Epo-Tek® ET353ND Heat Cure Epoxy (8oz)

Manufacturer Part Number:

ET353ND-8OZ

Click here for more details on the Epo-Tek® ET353ND Heat Cure Epoxy (8oz)

EPO-TEK® 353ND PART B

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

8.2. Appropriate engineering controls

Appropriate engineering controls : Ensure good ventilation of the work station.

Environmental exposure controls : Avoid release to the environment.

8.3. Individual protection measures/Personal protective equipment

Hand protection

Wear suitable gloves resistant to chemical penetration. Neoprene or nitrile rubber gloves. Butyl-rubber protective gloves. Choosing the proper glove is a decision that depends not only on the type of material, but also on other quality features, which differ for each manufacturer. Refer to manufacturer's information. Gloves must be replaced after each use and whenever signs of wear or perforation appear

Eye protection:

Safety glasses

Skin and body protection:

Wear suitable protective clothing

Respiratory protection:

Wear respiratory protection.

Personal protective equipment symbol(s):



Physical state





SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

: Liquid

Color : amber Odor : slight Odor threshold : No data available : No data available Melting point : Not applicable : No data available Freezing point **Boiling point** : No data available Flash point : No data available Relative evaporation rate (butyl acetate=1) : No data available Flammability (solid, gas) : Not applicable. Vapor pressure : No data available Relative vapor density at 20 °C : No data available Relative density : No data available Solubility : No data available Partition coefficient n-octanol/water (Log Pow) : No data available : No data available Auto-ignition temperature Decomposition temperature : No data available Viscosity, kinematic : No data available Viscosity, dynamic : No data available Explosion limits : No data available Explosive properties : No data available Oxidizing properties : No data available

2/15/2022 (Issue date) EN (English US) 5/13







Manufacturer: Epoxy Technology

Product Name:

Epo-Tek® ET353ND Heat Cure Epoxy (8oz)

Manufacturer Part Number:

ET353ND-8OZ

Click here for more details on the Epo-Tek® ET353ND Heat Cure Epoxy (8oz)

EPO-TEK® 353ND PART B

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

9.2. Other information

No additional information available

SECTION 10: Stability and reactivity

10.1. Reactivity

The product is non-reactive under normal conditions of use, storage and transport

10.2. Chemical stability

Stable under normal conditions.

10.3. Possibility of hazardous reactions

No dangerous reactions known under normal conditions of use.

10.4. Conditions to avoid

None under recommended storage and handling conditions (see section 7).

10.5. Incompatible materials

No additional information available

10.6. Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity (oral) : Harmful if swallowed. Acute toxicity (dermal) : Not classified Acute toxicity (inhalation) Not classified

EPO-TEK® 353ND PART B		
ATE US (oral)	490.339 mg/kg body weight	
Substituted imidazole		
ATE US (oral)	100 mg/kg body weight	
Imidazole (288-32-4)		
LD50 oral rat	970 mg/kg body weight (Equivalent or similar to OECD 401, Rat, Experimental value, Oral, 7 day(s))	
ATE US (oral)	960 mg/kg body weight	
Substituted anhydride		
LD50 oral rat	≈ 1144 mg/kg body weight Animal: rat, Guideline: OECD Guideline 401 (Acute Oral Toxicity), Remarks on results: other:	
LD50 dermal rabbit	400 – 640 mg/kg body weight Animal: rabbit, Guideline: OECD Guideline 402 (Acute Dermal Toxicity)	
ATE US (oral)	500 mg/kg body weight	
ATE US (dermal)	400 mg/kg body weight	

2/15/2022 (Issue date) Data is subject to change without notice. EN (English US) 6/13







Manufacturer: Epoxy Technology

Product Name:

Epo-Tek® ET353ND Heat Cure Epoxy (8oz)

Manufacturer Part Number:

ET353ND-8OZ

Click here for more details on the Epo-Tek® ET353ND Heat Cure Epoxy (8oz)

EPO-TEK® 353ND PART B

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Substituted imidazole	
LD50 oral rat	350 mg/kg Source: IUCLID
LD50 dermal rabbit	440 mg/kg Source: IUCLID
ATE US (oral)	173 mg/kg body weight
ATE US (dermal)	440 mg/kg body weight
Substituted imidazole	
LD50 oral rat	731 mg/kg (Equivalent or similar to OECD 401, Rat, Male / female, Experimental value, Oral)
LD50 dermal rabbit	> 400 mg/kg (Equivalent or similar to OECD 402, 24 h, Rabbit, Male / female, Experimental value, Dermal)
LC50 Inhalation - Rat	> 0.03 mg/l (Equivalent or similar to OECD 403, 8 h, Rat, Male / female, Experimental value, (maximum achievable concentration), Inhalation (vapours))
ATE US (oral)	731 mg/kg body weight
Skin corrosion/irritation	: Causes severe skin burns.
Serious eye damage/irritation	: Causes serious eye damage.
Respiratory or skin sensitization	: May cause an allergic skin reaction.
Germ cell mutagenicity	: Not classified
Carcinogenicity	: Suspected of causing cancer.
Substituted imidazole	
IARC group	2B - Possibly carcinogenic to humans
Reproductive toxicity	: May damage fertility or the unborn child.
STOT-single exposure	: Not classified
Substituted imidazole	
STOT-single exposure	May cause respiratory irritation.
STOT-repeated exposure	: Not classified
lmidazole (288-32-4)	
NOAEL (oral,rat,90 days)	80 mg/kg body weight Animal: rat, Guideline: OECD Guideline 408 (Repeated Dose 90-Day Oral Toxicity in Rodents)
Substituted anhydride	
NOAEL (oral.rat.90 days)	90 mg/kg body weight Animal: rat, Guideline: OECD Guideline 408 (Repeated Dose 90-Day Oral Toxicity Study in Rodents), Guideline: EPA OPPTS 870.3100 (90-Day Oral Toxicity in Rodents)
Substituted imidazole	
NOAEL (oral,rat,90 days)	150 mg/kg body weight Animal: rat, Guideline: OECD Guideline 422 (Combined Repeated Dose Toxicity Study with the Reproduction / Developmental Toxicity Screening Test), Guideline: other:EPA OPPTS 870.3850 (Combined Repeated Dose Toxicity Study with the Reproduction/Developmental Toxicity Screening Test)
Aspiration hazard	: Not classified
Viscosity, kinematic	: No data available
Symptoms/effects after skin contact	: Burns. May cause an allergic skin reaction.
Symptoms/effects after eye contact	: Serious damage to eyes.
Symptoms/effects after ingestion	: Burns.

2/15/2022 (Issue date) 7/13 EN (English US)





Manufacturer: Epoxy Technology

Product Name:

Epo-Tek® ET353ND Heat Cure Epoxy (8oz)

Manufacturer Part Number:

ET353ND-8OZ

Click here for more details on the Epo-Tek® ET353ND Heat Cure Epoxy (8oz)

EPO-TEK® 353ND PART B

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

SECTION 12: Ecological information		
12.1. Toxicity		
Ecology - general	: Before neutralisation, the product may represent a danger to aquatic organisms.	
Imidazole (288-32-4)		
LC50 - Fish [1]	283.6 mg/l (48 h, Leuciscus idus, Static system, Fresh water, Experimental value, Nominal concentration)	
EC50 - Crustacea [1]	341.5 mg/l (EU Method C.2, 48 h, Daphnia magna, Static system, Fresh water, Experimental value, Locomotor effect)	
ErC50 algae	133 mg/l (DIN 38412: German standard methods for the examination of water, waste water and sludge, 72 h, Desmodesmus subspicatus, Static system, Fresh water, Experimental value, Nominal concentration)	
NOEC chronic algae	25 mg/l	
Substituted anhydride		
LC50 - Fish [1]	100 – 215 mg/l Test organisms (species): Leuciscus idus	
EC50 - Crustacea [1]	267.94 mg/l Test organisms (species): Daphnia magna	
Substituted imidazole		
LC50 - Fish [1]	0.34 mg/l Source: IUCLID	
EC50 - Crustacea [1]	180 mg/l Source: IUCLID	
Substituted imidazole	·	
LC50 - Fish [1]	68.1 mg/l (DIN 38412-15, 96 h, Leuciscus idus, Static system, Fresh water, Experimental value)	
EC50 - Crustacea [1]	297.3 mg/l (EU Method C.2, 48 h, Daphnia magna, Static system, Fresh water, Experimental value)	
12.2. Persistence and degradability		
Imidazole (288-32-4)		
Persistence and degradability	Readily biodegradable in the soil. Readily biodegradable in water.	
Substituted anhydride		
Persistence and degradability	Not readily biodegradable in water.	
Substituted imidazole	•	
Persistence and degradability	Inherently biodegradable.	
Biochemical oxygen demand (BOD)	0.000002 g O□/g substance	
Chemical oxygen demand (COD)	0.0015 g O⊡/g substance	
Substituted imidazole		
Persistence and degradability	Readily biodegradable in water.	
12.3. Bioaccumulative potential		
Imidazole (288-32-4)		
Partition coefficient n-octanol/water (Log Pow)	-0.02 (Weight of evidence approach, OECD 107: Partition Coefficient (n-octanol/water): Shake Flask Method, 25 °C)	
2/15/2022 (Issue date)	EN (English US) 8/13	

Data is subject to change without notice.



Contact the professionals at Fiber Optic Center for a quote or to get more details.



Manufacturer: Epoxy Technology

Product Name:

Epo-Tek® ET353ND Heat Cure Epoxy (8oz)

Manufacturer Part Number:

ET353ND-8OZ

Click here for more details on the Epo-Tek® ET353ND Heat Cure Epoxy (8oz)

EPO-TEK® 353ND PART B

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Imidazole (288-32-4)		
Bioaccumulative potential	Not bioaccumulative.	
Substituted anhydride		
Partition coefficient n-octanol/water (Log Pow) -0.06 Source: ChemIDplus		
Substituted imidazole		
Partition coefficient n-octanol/water (Log Pow)	0.35 (Experimental value)	
Bioaccumulative potential	Low potential for bioaccumulation (Log Kow < 4).	
Substituted imidazole		
Partition coefficient n-octanol/water (Log Pow)	1.13 (Experimental value, OECD 107: Partition Coefficient (n-octanol/water): Shake Flask Method, 25 °C)	
Bioaccumulative potential	Low potential for bioaccumulation (Log Kow < 4).	

12.4. Mobility in soil

Imidazole (288-32-4)		
Surface tension	No data available in the literature	
Organic Carbon Normalized Adsorption Coefficient (Log Koc)	1.38 – 2.32 (log Koc, Calculated value)	
Ecology - soil	Low potential for adsorption in soil.	
Substituted anhydride		
Mobility in soil	15.75 Source: Quantitative Structure Activity Relation	
Substituted imidazole		
Mobility in soil	28.23 Source: EPI SUITE	
Ecology - soil	No (test)data on mobility of the substance available.	
Substituted imidazole		
Organic Carbon Normalized Adsorption Coefficient (Log Koc)	3.71 (log Koc, Calculated value, pH = 7)	

12.5. Other adverse effects

No additional information available

SECTION 13: Disposal considerations

13.1. Disposal methods

Waste treatment methods : Dispose of contents/container in accordance with licensed collector's sorting instructions

SECTION 14: Transport information

In accordance with DOT / TDG / IMDG / IATA

2/15/2022 (Issue date) EN (English US) 9/13







Manufacturer: Epoxy Technology


Product Name:

Epo-Tek® ET353ND Heat Cure Epoxy (8oz)

Manufacturer Part Number:

ET353ND-8OZ

Click here for more details on the Epo-Tek® ET353ND Heat Cure Epoxy (8oz)









Manufacturer:

Epoxy Technology

Product Name:

Epo-Tek® ET353ND Heat Cure Epoxy (8oz)

Manufacturer Part Number:

ET353ND-8OZ

Click here for more details on the Epo-Tek® ET353ND Heat Cure Epoxy (8oz)

44.5. Environmental hazarde	
14.5. Environmental hazards Other information	No control of the state of the
	: No supplementary information available.
14.6. Special precautions for user	
DOT UN-No.(DOT) DOT Special Provisions (49 CFR 172.102)	: UN3267 : IB3 - Authorized IBCs: Metal (31A, 31B and 31N); Rigid plastics (31H1 and 31H2); Composite (31HZ1 and 31HA2, 31HB2, 31HN2, 31HD2 and 31HH2). Additional Requirement: Only liquid with a vapor pressure less than or equal to 110 kPa at 50 C (1.1 bar at 122 F), or 130 kPa at 5 C (1.3 bar at 131 F) are authorized, except for UN2672 (also see Special Provision IP8 in Tabl 2 for UN2672). T7 - 4 178.274(d)(2) Normal
	material, as defined in 178.275 of this subchapter, where the test pressure is 1.5 times the MAWP.
DOT Packaging Exceptions (49 CFR 173.xxx) DOT Packaging Non Bulk (49 CFR 173.xxx)	: 154 : 203
DOT Packaging Bulk (49 CFR 173.xxx)	: 241
OOT Quantity Limitations Passenger aircraft/rail (49 CFR 173.27)	: 5L
DOT Quantity Limitations Cargo aircraft only (49 CFR 175.75)	: 60 L
DOT Vessel Stowage Location	 A - The material may be stowed "on deck" or "under deck" on a cargo vessel and on a passenger vessel.
DOT Vessel Stowage Other	: 40 - Stow "clear of living quarters",52 - Stow "separated from" acids
TDG	: UN3267
UN-No. (TDG) TDG Special Provisions	 10-(1) The technical name of at least one of the most dangerous substances that predominar contributes to the hazard or hazards posed by the dangerous goods must be shown, in parentheses, on the shipping document following the shipping name in accordance with clause 3.5(1)(c)(ii)(A) of Part 3 (Documentation). The technical name must also be shown, in parentheses, on a small means of containment or on a tag following the shipping name in accordance with subsections 4.11(2) and (3) of Part 4 (Dangerous Goods Safety Marks). (2) Despite subsection (1), the technical name for the following dangerous goods is not require to be shown on a shipping document or on a small means of containment when Canadian law domestic transport or an international convention for international transport prohibits the disclosure of the technical name: (a) UN1544, ALKALOID SALTS, SOLID, N.O.S. or ALKALOIDS, SOLID, N.O.S; (b) UN1851, MEDICINE, LIQUID, TOXIC, N.O.S. (c) UN3140, ALKALOID SALTS, LIQUID, N.O.S. or ALKALOIDS, LIQUID, N.O.S; (d) UN3249, MEDICINE, LIQUID, TOXIC, N.O.S. (e) UN3249, MEDICINE, SOLID, TOXIC, N.O.S.
Explosive Limit and Limited Quantity Index Excepted quantities (TDG) Passenger Carrying Road Vehicle or Passenger	(3) Despite subsection (1), the technical name for the following dangerous goods is not require to be shown on a small means of containment: (a) UN2814, INFECTIOUS SUBSTANCE, AFFECTING HUMANS; or (b) UN2900, INFECTIOUS SUBSTANCE, AFFECTING ANIMALS. 5 L E1 5 L
Carrying Railway Vehicle Index Emergency Response Guide (ERG) Number	: 153





Manufacturer: Epoxy Technology

Product Name:

Epo-Tek® ET353ND Heat Cure Epoxy (8oz)

Manufacturer Part Number:

ET353ND-8OZ

Click here for more details on the Epo-Tek® ET353ND Heat Cure Epoxy (8oz)

EPO-TEK® 353ND PART B

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

IMDG

Special provision (IMDG) : 223, 274 Limited quantities (IMDG) : 5 L Excepted quantities (IMDG) Packing instructions (IMDG) : P001, LP01 : IBC03 IBC packing instructions (IMDG) Tank instructions (IMDG) : T7 : TP1, TP28 Tank special provisions (IMDG)

EmS-No. (Fire) : F-A - FIRE SCHEDULE Alfa - GENERAL FIRE SCHEDULE EmS-No. (Spillage) : S-B - SPILLAGE SCHEDULE Bravo - CORROSIVE SUBSTANCES

Stowage category (IMDG)

Properties and observations (IMDG) : Reacts violently with acids. Causes burns to skin, eyes and mucous membranes.

PCA Excepted quantities (IATA) : E1 PCA Limited quantities (IATA) : Y841 PCA limited quantity max net quantity (IATA) : 1L PCA packing instructions (IATA) : 852 PCA max net quantity (IATA) : 5L CAO packing instructions (IATA) CAO max net quantity (IATA) : 60L Special provision (IATA) : A3, A803 ERG code (IATA) : 8L

14.7. Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable

SECTION 15: Regulatory information

15.1. US Federal regulations

All components of this product are present and listed as Active on the United States Environmental Protection Agency Toxic Substances Control Act

15.2. International regulations

CANADA

Substituted imidazole

Listed on the Canadian DSL (Domestic Substances List)

lmidazole (288-32-4)

Listed on the Canadian DSL (Domestic Substances List)

Substituted anhydride

Listed on the Canadian DSL (Domestic Substances List)

Substituted imidazole

Listed on the Canadian NDSL (Non-Domestic Substances List)

Substituted imidazole

Listed on the Canadian DSL (Domestic Substances List)

2/15/2022 (Issue date) EN (English US)







Manufacturer: Epoxy Technology

Product Name:

Epo-Tek® ET353ND Heat Cure Epoxy (8oz)

Manufacturer Part Number:

ET353ND-8OZ

Click here for more details on the Epo-Tek® ET353ND Heat Cure Epoxy (8oz)

EPO-TEK® 353ND PART B

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

EU-Regulations

No additional information available

National regulations

nidazole (288-32-4)

Listed on INSQ (Mexican National Inventory of Chemical Substances)

Substituted anhydride

Listed on INSQ (Mexican National Inventory of Chemical Substances)

Substituted imidazole

Listed on IARC (International Agency for Research on Cancer)

15.3. US State regulations



This product can expose you to Substituted imidazole, which is known to the State of California to cause cancer. For more information go to www.P65Warnings.ca.gov.

SECTION 16: Other information

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Full text of H-phrases	
H301	Toxic if swallowed
H302	Harmful if swallowed
H311	Toxic in contact with skin
H312	Harmful in contact with skin
H314	Causes severe skin burns and eye damage
H315	Causes skin irritation
H317	May cause an allergic skin reaction
H318	Causes serious eye damage
H335	May cause respiratory irritation
H351	Suspected of causing canoer
H360	May damage fertility or the unborn child

Safety Data Sheet (SDS), USA

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.

EN (English US)

2/15/2022 (Issue date)

13/13

