

**Manufacturer:**

FiberSource

Product Name:FiberSource LC Connector, Multimode, 127µm (micron)
Ceramic Ferrule, 3mm White Boot**Manufacturer Part Number:**

FS01127



▶ [Click here for more details on the FiberSource LC Connector, Multimode, 127µm \(micron\) Ceramic Ferrule, 3mm White Boot](#)

**Features:**

- Based on IEC 61754-20: LC Type Connector
- Ferrule ID: 127µm
- Meets UL94-VO Flammability Requirements
- Fiber Types: 50/125 or 62.5/125
- Insertion Loss: ≤0.4dB (MM)
- Operational Temperature: -40°C~+85°C
- Temperature Stability: ≤0.3dB(-40°C~+85°C)
- Mating Durability: ≤0.4dB(500 times)
- Housing Color: Beige
- Over Molded Dust Cap
- Made in the U.S.A.

Part Number: FS01125 LC MM OTW Simplex for 1.6/2.0mm Cable
FS01127 LC MM OTW Simplex for 3.0mm Cable
FS00821 LC MM OTW Simplex with Short Boot

Contact the professionals at Fiber Optic Center for a quote or to get more details.

focenter.com • 508-992-6464 | (800) 473-4237 • sales@focenter.com

23 Centre Street • New Bedford, MA 02740 USA

Product specifications and data are subject to change without notice. FOC last update 3/6/2026.