

**Manufacturer:**

FiberSource

**Product Name:**FiberSource LC Connector, Singlemode, 125.5µm (micron)  
Ceramic Ferrule, 1.6-2.0mm White Short Boot**Manufacturer Part Number:**

FS00922

[Learn More](#)

▶ [Click here for more details on the FiberSource LC Connector, Singlemode, 125.5µm \(micron\) Ceramic Ferrule, 1.6-2.0mm White Short Boot](#)

**Features:**

- Based on IEC 61754-20: LC Type Connector
- FOCIS 10a Compliant
- Meets UL94-VO Flammability Requirements
- Telcordia GR-326-CORE Tested
- Ferrule ID: 125.5µm (Standard) 125µm and 126µm Special Order
- Insertion Loss:  $\leq 0.25\text{dB}$
- Return Loss:  $\geq 55\text{dB}$
- Operational Temperature:  $-40^{\circ}\text{C} \sim +85^{\circ}\text{C}$
- Temperature Stability:  $\leq 0.3\text{dB} (-40^{\circ}\text{C} \sim +85^{\circ}\text{C})$
- Mating Durability:  $\leq 0.2\text{dB} (500 \text{ times})$
- Housing Color: Blue
- 19mm Short Boot
- Over Molded Dust Cap
- Made in the U.S.A.

Part Number: FS00922 LC SM OTW Simplex with Short Boot

**Contact the professionals at Fiber Optic Center for a quote or to get more details.**

[focenter.com](http://focenter.com) • 508-992-6464 | (800) 473-4237 • [sales@focenter.com](mailto:sales@focenter.com)

23 Centre Street • New Bedford, MA 02740 USA

Product specifications and data are subject to change without notice. FOC last update 3/3/2026.