


Model Number: 6679SP
Model Name: VistaTwist 3 w/ VistaTree House
Size: Length: 26'
Width: 23'-6"
Height: 18'-7"
Fall Height: 10'
Foundations: 9
Concrete Volume: 3.6 cubic yards
COMPLIANT WITH: ASTM F-1487
CSA Z614

Ages: 5-12 years
Use Zone: Length: 38'-10"
Width: 35'-6"



Technical Details:

Frame

Main Structure shall be 5-1/2" (139.8mm) diameter steel tubing combined with 4-1/2" (114.3mm) diameter steel tubing and 2-3/8" (60.5mm) diameter steel tubing, which after fabrication shall be powder coated in accordance with the specifications herein.

Climbing Nets

20mm diameter rope consists of 6 main strands, each strand containing 24 galvanized steel reinforcing strands within a polyamide sleeve, wrapped around a solid polyamide core for a total of 144 reinforcing strands. Ropes shall achieve a Class 7-8 colorfastness rating.

Rope Ball Connectors

One-piece compressed aluminum ball connector, compressed in place with 150,000 pounds source (667kN) to prevent the connection from moving and causing premature cable wear.

Rope End Fittings

One-piece compressed stainless steel end fitting.

Climber Pipe Junctions

11-3/4"(300mm) and 7-3/4" (200mm) diameter structural aluminum balls with aluminum covers. Shall be powder coated in accordance with the specifications herein.

Tensioning

Tensioning is achieved by way of a galvanized shackle and stainless steel eyebolt located at each Climber Pipe Junction capable of drawing the cables a minimum of 4"(100mm)

Decking

Constructed of 3/16" (5mm) thick steel. Deck sections are dipped in a phthlate-free textured slip-resistant polyvinyl chloride plastisol coating.

Rotomolded Components

Shall be uniform construction with rotationally molded linear low-density U.V. stabilized polyethylene with a 1/4" (6mm) nominal wall thickness, available in manufacturer's standard colors.

Flexible Surfaces

3/8" (10mm) thick textile-reinforced rubber belt.

Fasteners

All fasteners shall be stainless steel with locking patch or locking compound.

Metal Finish

Polyester (Powder) Coating – The polyester coating shall be uniformly applied by the electrostatic method to a minimum thickness of four mils. Promptly after application of the powder, the coating shall be oven-cured at 350 degrees Fahrenheit. The color(s) of the polyester coating shall be from the manufacturer's standard color selection.

Installation

Installation recommended by a licensed playground contractor, trained and certified on the applicable playground installation methods and standards, preferably certified by manufacturer or National Playground Contractors Association.