



Evo dual



Evo dual wall




Equipment

Control accessories:

page 327

pages 326-333

pages 334-335



Pendant



Wall




*Finished luminaire. Includes power cable and end caps.

Technical Information

Power	49W / 61W / 73W / 86W
Lumens	4.410 lm - 11.696 lm
Installation	Pendant / Wall
Material	Aluminium 6063
PCB	Flex / Rigid

Code	Installation	Size (Power)	CCT (lm/W)	Driver	Colour
Code 5	Pendant 3	1.130mm (49W) 4	Down-Up 2.700K (124 lm/W) 2	On / Off 1	<input type="checkbox"/> White (9003) 1
	Wall 7	1.410mm (61W) 5	Down-Up 3.000K (128 lm/W) 3	Dali 2	<input checked="" type="checkbox"/> Black (9005) 2
		1.690mm (73W) 6	Down-Up 4.000K (136 lm/W) 4	Push 3	<input checked="" type="checkbox"/> Custom RAL
		1.970mm (86W) 7	Down-Up RGB (100 lm/W) 8	Casambi 5	
			Down-Up 1.800-4.000K (90 lm/W) 9	Tuya 7	
			Down 1.800-4.000K Up RGB C		
			Down 2.700K Up RGB D		
			Down 3.000K Up RGB T		
			Down 4.000K Up RGB Q		

Code: **5**



Consult delivery terms and conditions.

*Create your code according to your preferences. RGB and CCT 1.800-4.000K only works with driver 5 Casambi and 7 Tuya.

