






Evo E



*Finished luminaire. Includes driver, spring clips, power cable and end caps.

Control accessories:  page 327

 pages 326-333


 pages 334-335


Technical Information

Power	10W / 21W / 31W / 42W / 52W / 63W / 73W
Lumens	860 lm - 8.833 lm
Installation	Recessed
Material	Aluminium 6063
PCB	Rigid

Code	Diffuser (Angle)	Size (Power)	CCT (lm/W)	Driver	Colour
Code 5	Black Slats (30°) C	280mm (10W) 1	2.700K (91-104 lm/W) 2	On / Off 1	<input type="checkbox"/> White (9003) 1
	White Slats (30°) F	560mm (21W) 2	3.000K (96-109 lm/W) 3	Dali 2	<input checked="" type="checkbox"/> Black (9005) 2
	Black Slats (60°) N	840mm (31W) 3	4.000K (104-121 lm/W) 4	Push 3	<input checked="" type="checkbox"/> Custom RAL
	White Slats (60°) P	1.120mm (42W) 4	RGB-W (86 lm/W) 8	Casambi 5	
		1.400mm (52W) 5	2.700-6.500K (95-105 lm/W) 9	Tuya 7	
		1.680mm (63W) 6			
		1.960mm (73W) 7			

Code: **5**



 Consult delivery terms and conditions.

*Create your code according to your preferences. RGB-W and CCT 2.700-6.500K only works with driver 5 Casambi and 7 Tuya.

