




Filter



Equipment

Code **30** recessed driver

Code **37** surface driver



*Finished luminaire. Includes suspension kit, power cable and end caps.

Control accessories: page 327

pages 326-333

pages 334-335




Technical Information

Power	Monocolor: 32W / 48W / 64W / 80W - RGB: 46W / 69W / 92W / 120W
Lumens	3.200 lm - 13.320 lm
Installation	Pendant
Material	Aluminium and polycarbonate
Material	Flex (Fine 48 / Fine 54)

Code / Diffuser (Angle)	Size (Power Monocolor - RGB)	CCT (lm/W)	Driver	Colour
Recessed Opal (360°) 30	800mm (32W) - (46W) 3	2.700K (100 lm/W) 2	On / Off 1	○ White (9003) 1
Surface Opal (360°) 37	1.200mm (48W) - (69) 5	3.000K (105 lm/W) 3	Dali 2	● Black (9005) 2
	1.600mm (64W) - (92) 7	4.000K (111 lm/W) 4	Push 3	
	2.000mm (80W) - (120W) 9	RGB (58 lm/W) 7	Casambi 5	
			Tuya 7	

Code:



ⓘ Consult delivery terms and conditions.

*Create your code according to your preferences. RGB only works with driver 5 Casambi and 7 Tuya.

