




Oxo r dimm recessed

Oxo sq dimm recessed



Ø63mm

Ø109mm

Ø63mm

109x109mm



RECESSED

Technical Information

Power	12W	12W
Driver	40 VDC 300 mA	40 VDC 300 mA
Installation	Recessed	Recessed
Color Temperature	Switch 2.700K / 3.200K / 4.000K	Switch 2.700K / 3.200K / 4.000K
Lumens	1.260 lm	1.260 lm
Material	Aluminium	Aluminium
Finishes	White / Black	White / Black
Code	<input type="radio"/> 4457-D(N) <input type="radio"/> 4458-D(N) <input checked="" type="radio"/> Custom RAL	<input type="checkbox"/> 4459-D(N) <input type="checkbox"/> 4460-D(N) <input checked="" type="checkbox"/> Custom RAL


Accessories



Included with:
4457-D(N) / 4459-D(N)



Included with:
4457-D(N) / 4458-D(N) / 4459-D(N) / 4460-D(N)



Consult delivery terms and conditions.

3 YEARS WARRANTY | 30.000 HOURS | → | IP 20 | 220/240 VAC | UGR <14 | PF >0,9 | CRI ≥90 | 15° / 38° / 60° | 50/60 Hz | TRIAC DIMM | | +50°C / -20°C | CCT SWITCH | 1/20