



Mini Thesis recessed


Thesis recessed




Thesis XL recessed



Ø125mm 

Ø195mm 

Ø230mm 














Technical Information

Power	15W	25W	35W
Driver	DOB	DOB	DOB
Installation	Recessed	Recessed	Recessed
Color Temperature	Switch 3.000K / 4.000K / 5.000K	Switch 3.000K / 4.000K / 5.000K	Switch 3.000K / 4.000K / 5.000K
Lumens	1.300 lm	2.625 lm	3.100 lm
Material	Polybutylene and Polycarbonate	Polybutylene and Polycarbonate	Polybutylene and Polycarbonate
Finishes	White / Black	White / Black	White

Code	<input type="radio"/> 4766	<input type="radio"/> 4236	<input type="radio"/> 5030
	<input checked="" type="radio"/> 4987	<input checked="" type="radio"/> 4988	<input checked="" type="radio"/> Custom RAL
	<input checked="" type="radio"/> Custom RAL	<input checked="" type="radio"/> Custom RAL	
	UGR <19   <input type="checkbox"/> 1/10	UGR <19   <input type="checkbox"/> 1/6	<input type="checkbox"/> 1/6



 Consult delivery terms and conditions.

 3 YEARS WARRANTY | 
  25.000 HOURS | 
  IP 40 | 
  220/240 VAC | 
  PF >0,9 | 
  CRI ≥85 | 
  90° | 
  50/60 Hz | 
  IK06 | 
  +40°C / -20°C | 
  CCT SWITCH