


Triton down




*Finished luminaire. Includes power supply, 2mts power cable and end caps.

Control accessories:  pages 334-335




Technical Information

Power	46W / 57W / 69W / 80W / 103W
Lumens	5.152 lm - 14.008 lm
Installation	Surface / Pendant
Material	Aluminium 6063
PCB	Rigid

Code	Diffuser (Angle)	Size (Power)	CCT (lm/W)	Driver	Colour
Code 4	Opal (80°) 6	1.130mm (46W) 3	2.700K (112 lm/W) 2	On / Off 1	<input type="checkbox"/> White (9003) 1
		1.410mm (57W) 4	3.000K (128 lm/W) 3	Dali 2	<input type="checkbox"/> Black (9005) 2
		1.690mm (69W) 5	4.000K (136 lm/W) 4		<input checked="" type="radio"/>  Custom RAL
		1.970mm (80W) 6	5.500K (136 lm/W) 5		
		2.530mm (103W) 7			

Code: **4** **6**

 Consult delivery terms and conditions.
*Create your code according to your preferences.

Accessories

					
Wall bracket <input type="checkbox"/> 40531 <input checked="" type="checkbox"/> 40532	Ceiling suspension <input checked="" type="checkbox"/> 40510	Suspension Kit <input checked="" type="checkbox"/> 40520 (2m)	Linear Joint IP68 Ø26x95mm <input checked="" type="checkbox"/> 5671	T Joint IP68 74x118mm <input checked="" type="checkbox"/> 5672	X Joint IP68 122x122mm <input checked="" type="checkbox"/> 5673

