



Urban



Control accessories: page 327 pages 326-333 pages 334-335

Technical Information

Power	46W / 57W / 69W / 80W / 103W
Lumens	4.830 lm - 14.008 lm
Installation	Surface / Pendant
Material	Aluminium 6063
PCB	Rigid

Code	Diffuser (Angle)	Size (Power)	CCT (lm/W)	Driver	Colour
Code 6	UGR (78°) 4	1.130mm (46W) 3	2.700K (112 lm/W) 2	On / Off 1	<input type="checkbox"/> White (9003) 1
	Opal (112°) 5	1.410mm (57W) 4	3.000K (128 lm/W) 3	Dali 2	<input type="checkbox"/> Black (9005) 2
		1.690mm (69W) 5	4.000K (136 lm/W) 4	Push 3	<input type="checkbox"/> Gray (9006) 3
		1.970mm (80W) 6	5.000K (136 lm/W) 5	Casambi 5	<input type="checkbox"/> Matt Gold 4
		2.530mm (103W) 7	2.700-5.500K (105 lm/W) 9	Tuya 7	<input type="checkbox"/> Corten 6
					<input type="checkbox"/> Copper 7
					<input type="checkbox"/> Custom RAL 7


Code: **6**

Consult delivery terms and conditions.

*Create your code according to your preferences. CCT 2.700-5.500K only works with driver 5 Casambi and 7 Tuya.

Accessories

End caps <input type="checkbox"/> 40721 <input type="checkbox"/> 40722 <input type="checkbox"/> 40723	Joint 180° <input type="checkbox"/> 40220	Joint 90° <input type="checkbox"/> 40550	Joint 90° <input type="checkbox"/> 40610	Wall bracket <input type="checkbox"/> 40851 <input type="checkbox"/> 40852 <input type="checkbox"/> 40853	Trimless <input type="checkbox"/> 40669	Base 3x0,75 (2,5m) Ø60x28mm <input type="checkbox"/> 40881 <input type="checkbox"/> 40882 <input type="checkbox"/> 40883	Base 5x0,5 (2,5m) Ø60x28mm <input type="checkbox"/> 40991 <input type="checkbox"/> 40992 <input type="checkbox"/> 40993	Ceiling suspension <input type="checkbox"/> 40780	Suspension Kit <input type="checkbox"/> 40795 (5m)



Accessories pages 176-179.

|
 |
 |
 |
 |
 |
 |
 |
 |
 |
 |
 |
 |
 |