



Urban E



*Spring clips included.

Control accessories: page 327

pages 326-333

pages 334-335



Technical Information

Power	46W / 57W / 69W / 80W / 103W	Material	Aluminium 6063
Lumens	4.830 lm - 14.008 lm	PCB	Rigid
Installation	Recessed		

Code	Diffuser (Angle)	Size (Power)	CCT (lm/W)	Driver / Emergency	Colour
Code 3	UGR (78°) 4	1.130mm (46W) 3	2.700K (112 lm/W) 2	On / Off 1	<input type="checkbox"/> White (9003) 1
	Opal (112°) 5	1.410mm (57W) 4	3.000K (128 lm/W) 3	Dali 2	<input checked="" type="checkbox"/> Black (9005) 2
		1.690mm (69W) 5	4.000K (136 lm/W) 4	Push 3	<input type="checkbox"/> Gray (9006) 3
		1.970mm (80W) 6	5.000K (136 lm/W) 5	Casambi 5	<input checked="" type="checkbox"/> Custom RAL
		2.530mm (103W) 7	2.700-5.500K (105 lm/W) 9	Tuya 7	
				Emergency + On / Off K1	
				Emergency + Dali K2	
				Emergency + Push K3	
				Emergency + Casambi K5	

Code: **3**

Accessories pages 176-179.

Consult delivery terms and conditions.

*Create your code according to your preferences. CCT 2.700-5.500K only works with driver 5 Casambi and 7 Tuya.

Accessories

