


Urban market




Control accessories:  pages 334-335



Technical Information


Power	45W / 55,5W / 66W / 76,5W / 97,5W
Lumens	5.040 lm - 13.552 lm
Installation	Surface / Pendant
Material	Aluminium 6063
PCB	Rigid


Code	Diffuser (Angle)	Size (Power)	CCT (lm/W)	Driver	Colour
Code 2	Asymmetric (15°/60°) 1	1.130mm (45W) 3	3.000K (112 lm/W) 3	On / Off 1	<input type="checkbox"/> White (9003) 1
	Double asym.(60°/60°) 2	1.410mm (55,5W) 4	4.000K (118 lm/W) 4	Dali 2	<input checked="" type="checkbox"/> Black (9005) 2
	Optical (30°) 3	1.690mm (66W) 5	MEAT R - 3.200K (86 lm/W) R		<input checked="" type="checkbox"/>  Custom RAL
	Optical (60°) 6	1.970mm (76,5W) 6	HAM - 3.200K (85 lm/W) X		
	Optical (90°) 9	2.530mm (97,5W) 7	MEAT M - 3.500K (84 lm/W) M		
			FISH - 6.500K (139 lm/W) F		
			FRUIT - 4.200K (123 lm/W) V		
			BREAD - 2.700K (131 lm/W) P		

Code: **2**

 Consult delivery terms and conditions.
*Create your code according to your preferences.

Accessories

						
End caps <input type="checkbox"/> 40721 <input checked="" type="checkbox"/> 40722	Joint 180° <input checked="" type="checkbox"/> 40220	Joint 90° <input checked="" type="checkbox"/> 40550	Base 3x0,75 (2,5m) Ø60x28mm <input type="checkbox"/> 40881 <input checked="" type="checkbox"/> 40882	Base 5x0,5 (2,5m) Ø60x28mm <input type="checkbox"/> 40991 <input checked="" type="checkbox"/> 40992	Ceiling suspension <input checked="" type="checkbox"/> 40780	Suspension Kit <input checked="" type="checkbox"/> 40795 (5m)



Accessories pages 176-179.

5 YEARS WARRANTY	50.000 HOURS	IP 40	230 VAC	PF >0,9	CRI 80/93					3,37m Max		
----------------------------	------------------------	-----------------	-------------------	-------------------	---------------------	---	---	---	---	---------------------	---	---