



Urban train E




63mm x L

\*Finished luminaire.  
Includes clips, power cable and end caps.

Urban train



\*Finished luminaire.  
Includes suspension kit, power cable and end caps.



Control accessories:  pages 326-333

 pages 334-335



Technical Information


Power	46W / 57W / 69W / 80W
Lumens	4.830 lm - 10.880 lm
Installation	Recessed / Pendant

Material	Aluminium 6063
PCB	Rigid

Code	Diffuser (Angle)	Size (Power)	CCT (lm/W)	Driver / Emergency	Colour
Train E <b>8</b>	Black Slats (62°) <b>2</b>	1.130mm (46W) <b>3</b>	<b>2.700K</b> (112 lm/W) <b>2</b>	On / Off <b>1</b>	<input type="checkbox"/> White (9003) <b>1</b>
Train <b>6</b>	Alum. Slats (84°) <b>7</b>	1.410mm (57W) <b>4</b>	<b>3.000K</b> (128 lm/W) <b>3</b>	Dali <b>2</b>	<input checked="" type="checkbox"/> Black (9005) <b>2</b>
		1.690mm (69W) <b>5</b>	<b>4.000K</b> (136 lm/W) <b>4</b>	Push <b>3</b>	<input checked="" type="checkbox"/> Custom RAL
		1.970mm (80W) <b>6</b>	<b>5.000K</b> (136 lm/W) <b>5</b>	Casambi <b>5</b>	
			<b>2.700-5.500K</b> (105 lm/W) <b>9</b>	Emerg.+ On / Off <b>K1</b>	
				Emerg.+ Dali <b>K2</b>	
				Emerg.+ Push <b>K3</b>	
				Emerg.+ Casambi <b>K5</b>	

Code:

 Emergency  
4.000K 200lm |  1/3H.  
EN 60598-2-2



Accessories pages 176-179.  Consult delivery terms and conditions.

\*Create your code according to your preferences. CCT 2.700-5.500K only works with driver 5 Casambi.

