



Urban work E



63mm x L

\*Finished luminaire.  
Includes clips, power cable and end caps.


Urban work



\*Finished luminaire.  
Includes suspension kit, power cable and end caps.

Control accessories:  pages 326-333


 pages 334-335





Technical Information


Power	35W / 43W / 51W / 59W / 97,5W
Lumens	3.675 lm - 11.505 lm
Installation	Recessed / Pendant

Material	Aluminium 6063
PCB	Rigid

Code	Diffuser (Angle)	Size (Power)	CCT (lm/W)	Driver / Emergency	Colour
Work E <b>7</b>	Retracted (102°) <b>3</b>	1.130mm (35W) <b>3</b>	2.700K (105 lm/W) <b>2</b>	On / Off <b>1</b>	<input type="checkbox"/> White (9003) <b>1</b>
Work <b>6</b>		1.410mm (43W) <b>4</b>	3.000K (112 lm/W) <b>3</b>	Dali <b>2</b>	<input checked="" type="checkbox"/> Black (9005) <b>2</b>
		1.690mm (51W) <b>5</b>	4.000K (118 lm/W) <b>4</b>	Push <b>3</b>	 Custom RAL
		1.970mm (59W) <b>6</b>	5.000K (118 lm/W) <b>5</b>	Casambi <b>5</b>	
		2.530mm (97,5W) <b>7</b>	2.700-5.500K (105 lm/W) <b>9</b>	Emerg.+ On / Off <b>K1</b>	
				Emerg.+ Dali <b>K2</b>	
		Emerg.+ Push <b>K3</b>			
		Emerg.+ Casambi <b>K5</b>			

Code:

 Emergency  
4.000K 200lm |  1/3H.  
EN 60598-2-2



Accessories pages 176-179.  Consult delivery terms and conditions.

\*Create your code according to your preferences. CCT 2.700-5.500K only works with driver 5 Casambi and 7 Tuyu.

