
Nano Argo flat recessed








Argo recessed








Argo XL recessed







Technical Information

	Nano Argo flat recessed	Argo recessed	Argo XL recessed
Power	2W	3,5W	3,5W
Driver	3,3 VDC 200 mA	18 VDC 140 mA	18 VDC 140 mA
Installation	Recessed	Recessed	Recessed
Color Temperature	2.700K / 3.000K / 4.000K	2.700K / 3.000K / 4.000K	2.700K / 3.000K / 4.000K
Lumens	80 lm	125 lm	125 lm
Material	Aluminium and acrylic	Aluminium and acrylic	Aluminium and acrylic
Finishes	White / Black	White / Black	White / Black

Code									
	○	2.700K	5258	○	2.700K	5246	○	2.700K	5252
	○	3.000K	5259	○	3.000K	5247	○	3.000K	5253
	○	4.000K	5260	○	4.000K	5248	○	4.000K	5254
	●	2.700K	5261	●	2.700K	5249	●	2.700K	5255
	●	3.000K	5262	●	3.000K	5250	●	3.000K	5256
	●	4.000K	5263	●	4.000K	5251	●	4.000K	5257

CE RoHS EAC

3 YEARS WARRANTY | 35.000 HOURS | IP 20 | 220/240 VAC | PF >0,5 | CRI ≥90 | 180° | 50/60 Hz | +40°C -20°C | 1/100