
## Nano Argo flat recessed







## Argo recessed







## Argo XL recessed






## Technical Information

| | Nano Argo flat recessed | Argo recessed | Argo XL recessed |
|---|---|---|---|
| Power | 2W | 3,5W | 3,5W |
| Driver | 3,3 VDC 200 mA | 18 VDC 140 mA | 18 VDC 140 mA |
| Installation | Recessed | Recessed | Recessed |
| Color Temperature | 2.700K / 3.000K / 4.000K | 2.700K / 3.000K / 4.000K | 2.700K / 3.000K / 4.000K |
| Lumens | 80 lm | 125 lm | 125 lm |
| Material | Aluminium and acrylic | Aluminium and acrylic | Aluminium and acrylic |
| Finishes | White / Black | White / Black | White / Black |

| Code | | | | | | | | | |
|---|---|---|---|---|---|---|---|---|---|
| | ○ | 2.700K | 5258 | ○ | 2.700K | 5246 | ○ | 2.700K | 5252 |
| | ○ | 3.000K | 5259 | ○ | 3.000K | 5247 | ○ | 3.000K | 5253 |
| | ○ | 4.000K | 5260 | ○ | 4.000K | 5248 | ○ | 4.000K | 5254 |
| | ● | 2.700K | 5261 | ● | 2.700K | 5249 | ● | 2.700K | 5255 |
| | ● | 3.000K | 5262 | ● | 3.000K | 5250 | ● | 3.000K | 5256 |
| | ● | 4.000K | 5263 | ● | 4.000K | 5251 | ● | 4.000K | 5257 |

CE RoHS EAC

3 YEARS WARRANTY | 35.000 HOURS | IP 20 | 220/240 VAC | PF >0,5 | CRI ≥90 | 180° | 50/60 Hz | +40°C -20°C | 1/100