



EU REGULATION 812/2013


MODEL		EWH 80 SLIM	EWH 50 SLIM	EWH 80 H	EWH 50 H	EWH 100
Declared load profile		M	M	M	M	L
Water heating energy efficiency class		E	D	D	C	D
Water heating energy efficiency, η _{wh}	%	32	35	33	36	36
Annual energy consumption AEC	kWh/year	1602	1489	1554	1418	2820
Thermostat temperature settings Tout of the box	°C	75	75	75	75	75
Sound power level L _{WA}	dB	15	15	15	15	15

EU REGULATION 814/2013


Storage volume, V	75	47	73	46	100
The mixed water at 40 °C V40	103	69	133	76	159
Water heating energy efficiency, η _{wh}	32,1	34,5	33,0	36,2	36,3

CARACTERÍSTICAS


Average number of users	/2-4/	/2-3/	/2-4/	/2-3/	/3-5/
Horizontal installation	•	•	•	•	–
Sapphire enameled steel tank	•	•	•	•	•
Sapphire heating element	•	•	•	•	•
Temperature regulation (°C)	30-75°C	30-75°C	30-75°C	30-75°C	30-75°C
Maximum input pressure	0,75 Mpa	0,75 Mpa	0,75 Mpa	0,75 Mpa	0,75 Mpa
Thermometer	•	•	•	•	•
Magnesium protection anode	•	•	•	•	•
Maximum input temperatures (°C)	75°C	75°C	75°C	75°C	75°C
Overpressure protection	•	•	•	•	•
Protection against heating	•	•	•	•	•
Dry heating protection	•	•	•	•	•
Degree of protection against humidity	IPX4	IPX4	IPX4	IPX4	IPX4
Insulation thickness (mm)	18	18	20	20	20
External dimensions (H/A/D), mm	900/570/340	860/470/290	1030/385/425	711/385/425	972/450/470




EWH 100




EWH 80




EWH 50



EWH 30



EWH 15



EWH 80 H

EU REGULATION 812/2013


MODEL		EWH 80	EWH 50	EWH 30	EWH 15
Declared load profile		M	M	S	XXS
Water heating energy efficiency class		D	C	C	B
Water heating energy efficiency, η _{wh}	%	35	37	32	34
Annual energy consumption AEC	kWh/year	1461	1390	577	536
Thermostat temperature settings Tout of the box	°C	75	75	75	75
Sound power level L _{WA}	dB	15	15	15	15

EU REGULATION 814/2013


Storage volume, V	80	50	30	15
The mixed water at 40 °C V40	144	80	51	26
Water heating energy efficiency, η _{wh}	35,1	36,9	32	34,4

CARACTERÍSTICAS


Average number of users	/2-4/	/2-3/	/1-2/	1
Horizontal installation	–	–	–	–
Sapphire enameled steel tank	•	•	•	•
Sapphire heating element	•	•	•	•
Temperature regulation (°C)	30-75°C	30-75°C	30-75°C	30-75°C
Maximum input pressure	0,75 Mpa	0,75 Mpa	0,75 Mpa	0,75 Mpa
Thermometer	•	•	•	•
Magnesium protection anode	•	•	•	•
Maximum input temperatures (°C)	75°C	75°C	75°C	75°C
Overpressure protection	•	•	•	•
Protection against heating	•	•	•	•
Dry heating protection	•	•	•	•
Degree of protection against humidity	IPX4	IPX4	IPX4	IPX4
Insulation thickness (mm)	20	20	20	20
External dimensions (H/A/D), mm	806/450/470	579/450/470	602/340/360	397/340/360



EWH 50 H



EWH 80 SLM



EWH 50 SLIM

EWH 80 H · EWH 50 H

EWH 80 H SLIM · EWH 50 H SLIM



HORIZONTAL INSTALLATION



VERTICAL INSTALLATION



VERTICAL INSTALLATION



HORIZONTAL INSTALLATION