

PRODUCT FICHE ACCORDING TO COMMISSION DELEGATED REGULATION (EU) NO 65/2014

Model	HLB 860 P	HLB 840 P	HSB 635 P	HSB 630 P	HSB 625 P HSB 620 P
Energy Efficiency Index (EEI)	80,8	81	81	81	81
Energy Efficiency Class	A+	A+	A+	A+	A+
Energy consumption per cycle in conventional mode (kWh)	0,88	0,88	0,88	0,88	0,88
Energy consumption per cycle in fan-forced convection mode (kWh)	0,68	0,68	0,68	0,68	0,68
Number of cavities	1	1	1	1	1
Heat source	Electric	Electric	Electric	Electric	Electric
Volume (l)	70	70	70	70	70

DIMENSIONS

External, mm	595x595x 559	595x595x 559	595x595x 559	595x595x 559	595x595x 559
Inner cavity, mm	367x475x405	367x475x405	367x475x405	367x475x405	367x475x405

CLEANING SYSTEMS

DualClean	•	•	•	•	•
Pyrolytic	•	•	•	•	•
HydroClean®	PRO	PRO	PRO	PRO	PRO
Enamel	Slippery	Slippery	Slippery	Slippery	Slippery

FEATURES

Type	Pyrolytic Multifunction	Pyrolytic Multifunction	Pyrolytic Multifunction	Pyrolytic Multifunction	Pyrolytic Multifunction
Stainless steel (fingerprint proof)	•	• / White	•	White / Black	• / White / Black
Cooking functions	12	8	8	8	8
Temperature regulator	30-270°	50-250°	50-250°	50-250°	50-250°
Touch Control	• / TFT 4"	• / TFT 4"	• / LED display	• / LED display	• / LED display
LED ring illuminated knobs	•	-	-	-	-
SoftClose	•	•	-	-	-
Recipes	20 recipes	-	-	-	-
Meat probe	-	-	-	-	-
SlowCook: low temperature cooking	•	-	-	-	-
Tangential ventilation	Plus 2 speeds	Plus 2 speeds	Plus 2 speeds	Plus 2 speeds	Plus 2 speeds
Express quick heating	Automatic	•	•	•	•
Telescopic guides	1+1 Full easy slide	1 easy slide	1	1	-
Drop-down grill	-	-	-	-	-
Light	25W	25W	25W	25W	25W

SAFETY SYSTEMS

Full glazed door	4 removable	4 removable	4 removable	4 removable	3 removable
Automatic disconnection security system	•	•	•	•	•
Children safety	•	•	•	•	•
Grill protection	•	•	•	•	•
Anti-tip tray system	•	•	•	•	•

ACCESORIES

MultiCook / cast aluminium tray	optional	optional	optional	optional	optional
Anti-tip baking / deep tray (50 mm)	- / •	- / •	- / •	- / •	- / •
Anti-tip reinforced / cooking grid	• / -	• / -	- / •	- / •	- / •

POWER CONSUMPTION

Turbo, W	2.000	2.000	-	-	-
Grill / Maxi grill, W	1.050/2.450	1.050/2.450	1.050/2.450	1.050/2.450	1.050/2.450
Traditional, W	2.450	2.450	2.450	2.450	2.450
Multifunction motor, W	25	25	25	25	25
Bottom heat, W	1.050	1.050	1.050	1.050	1.050
Cooling fan motor, W	30	30	30	30	30

ELECTRICAL FEATURES

Voltage, V	220/240	220/240	220/240	220/240	220/240
Frequency, HZ	50/60	50/60	50/60	50/60	50/60
Maximum connection rating, W	3.552	3.552	3.552	3.552	3.552
Cable connection length, cm	150 + Plug	110	110	110	110

Model	IOVEN	HLB 860	HLB 850	HLB 840	HLB 830	HSB 645	HSB 640 BLACK HSB 640 WHITE	HSB 635
Energy Efficiency Index (EEI)	81	81	81	81	81	81	81	81
Energy Efficiency Class	A+	A+	A+	A+	A+	A+	A+	A+
Energy consumption per cycle in conventional mode (kWh)	0,83	0,83	0,81	0,81	0,81	0,81	0,81	0,86
Energy consumption per cycle in fan-forced convection mode (kWh)	0,68	0,68	0,68	0,68	0,68	0,68	0,68	0,68
Number of cavities	1	1	1	1	1	1	1	1
Heat source	Electric	Electric	Electric	Electric	Electric	Electric	Electric	Electric
Volume (l)	70	70	70	70	70	70	70	70

DIMENSIONS

External, mm	595x595x 559	595x595x 559	595x595x 559	595x595x 559	595x595x 559	595x595x 559	595x595x 559	595x595x 559
Inner cavity, mm	367x475x405	367x475x405	367x475x405	367x475x405	367x475x405	367x475x405	367x475x405	367x475x405

CLEANING SYSTEMS

DualClean	-	-	-	-	-	-	-	-
Pyrolytic	-	-	-	-	-	-	-	-
HydroClean®	PRO	PRO	PRO	PRO	PRO	PRO	PRO	PRO
Enamel	Slippery	Slippery	Slippery	Slippery	Slippery	Slippery	Slippery	Slippery

FEATURES

Type	Multifunction Turbo	Multifunction Turbo	Multifunction Turbo	Multifunction Turbo	Multifunction	Multifunction Turbo	Multifunction Turbo	Multifunction
Stainless steel (fingerprint proof)	•	•	•	• / White	•	•	•	•
Cooking functions	18	12	9	9	6	9	9	8
Temperature regulator	30-270°	30-270°	50-250°	50-250°	50-250°	50-250°	50-250°	50-250°
Touch Control	• / TFT 5"	• / TFT 4"	• / LED display	• / LED display	• / LED display	• / LED display	• / LED display	• / LED display
LED ring illuminated knobs	-	•	-	-	-	-	-	-
SoftClose	•	•	•	-	-	-	-	-
Recipes	50 recipes	20 recipes	-	-	-	-	-	-
Meat probe	•	-	-	-	-	-	-	-
SlowCook: low temperature cooking	•	•	-	-	-	-	-	-
Tangential ventilation	•	•	Dynamic	Dynamic	Dynamic	Dynamic	Dynamic	Dynamic
Express quick heating	Automatic	Automatic	•	•	•	•	•	•
Telescopic guides	2 Full easy slide	1 easy slide	1 easy slide	1 easy slide	1 easy slide	1 easy slide	1 easy slide	1 easy slide
Drop-down grill	•	•	•	•	-	-	-	-
Light	2 side LED, 4W	25W	25W	25W	25W	25W	25W	25W

SAFETY SYSTEMS

Full glazed door	3 removable	2 removable	3 removable	2 removable	2 removable	2 removable	2 removable	2 removable
Automatic disconnection security system	•	•	-	-	-	-	-	-
Children safety	•	•	•	•	•	•	•	•
Grill protection	•	•	•	•	•	•	•	•
Anti-tip tray system	•	•	•	•	•	•	•	•

ACCESORIES

MultiCook / cast aluminium tray	1 / optional	optional	optional	optional	optional	optional	optional	optional
Anti-tip baking / deep tray (50 mm)	1 / 1	- / •	• / •	- / •	- / •	• / •	• / •	• / •
Anti-tip reinforced / cooking grid	2 / -	• / -	• / -	• / -	- / •	- / •	- / •	- / •

POWER CONSUMPTION

Turbo, W	2.000	2.000	2.000	2.000	-	2.000	2.000	-
Grill / Maxi grill, W	1.100/2.500	1.100/2.500	1.100/2.500	1.100/2.500	1.100/2.500	1.100/2.500	1.100/2.500	1.100/2.500
Traditional, W	2.550	2.550	2.550	2.550	2.550	2.550	2.550	2.550
Multifunction motor, W	22	22	22	22	22	22	22	22
Bottom heat, W	1.150	1.150	1.150	1.150	1.150	1.150	1.150	1.150
Cooling fan motor, W	18	18	18	18	18	18	18	18

ELECTRICAL FEATURES

Voltage, V	220/240	220/240	220/240	220/240	220/240	220/240	220/240	220/240
Frequency, HZ	50/60	50/60	50/60	50/60	50/60	50/60	50/60	50/60
Maximum connection rating, W	3.198	3.215	3.215	3.215	2.615	3.215	3.215	2.615
Cable connection length, cm	150 + Plug	150 + Plug	110	110	110	110	110	110

PRODUCT FICHE ACCORDING TO COMMISSION DELEGATED REGULATION (EU) NO 65/2014

Model	HSB 630	HSB 615	HSB 610	HBB 605	HBB 535	HBB 510	HBB 435 HBB 490
Energy Efficiency Index (EEI)	81	84,7	84,7	84,7	94,8	94,8	95,3
Energy Efficiency Class	A+	A	A	A	A	A	A
Energy consumption per cycle in conventional mode (kWh)	0,86	0,82	0,82	0,82	0,83	0,83	0,81
Energy consumption per cycle in fan-forced convection mode (kWh)	0,68	0,71	0,71	0,71	-	-	-
Number of cavities	1	1	1	1	1	1	1
Heat source	Electric	Electric	Electric	Electric	Electric	Electric	Electric
Volume (l)	70	70	70	70	76	76	72

DIMENSIONS

External, mm	595x595x 559	595x595x 559	595x595x 559	595x595x 559	595x595x 559	595x595x 559	595x595x 559
Inner cavity, mm	367x475x405	367x475x405	367x475x405	367x475x405	367x475x441	367x475x441	367x475x441

CLEANING SYSTEMS

DualClean	-	-	-	-	-	-	-
Pyrolytic	-	-	-	-	-	-	-
HydroClean®	PRO	ECO	ECO	ECO	ECO	ECO	-
Enamel	Slippery	Slippery	Slippery	Slippery	Slippery	Slippery	Slippery

FEATURES

Type	Multifunction	Multifunction	Multifunction	Multifunction	Conventional	Conventional	Conventional
Stainless steel (fingerprint proof)	White/Black	•	White/Black	•	•	Black	White/Black
Cooking functions	8	6	6	6	3	3	3
Temperature regulator	50-250°	50-250°	50-250°	50-250°	50-250°	50-250°	50-250°
Touch Control	• / LED display	Minute Minder	Minute Minder	Minute Minder	Minute Minder	Minute Minder	-
LED ring illuminated knobs	-	-	-	-	-	-	-
SoftClose	-	-	-	-	-	-	-
Recipes	-	-	-	-	-	-	-
Meat probe	-	-	-	-	-	-	-
SlowCook: low temperature cooking	-	-	-	-	-	-	-
Tangential ventilation	Dynamic	Dynamic	Dynamic	Dynamic	Dynamic	Dynamic	Dynamic
Express quick heating	•	•	•	•	-	-	-
Telescopic guides	1 easy slide	1 easy slide	1 easy slide	-	-	-	-
Drop-down grill	-	-	-	-	-	-	-
Light	25W	25W	25W	25W	25W	25W	25W

SAFETY SYSTEMS

Full glazed door	2 removable	2 removable	2 removable	2 removable	2 removable	2 removable	2 removable
Automatic disconnection security system	-	-	-	-	-	-	-
Children safety	•	-	-	-	-	-	-
Grill protection	•	•	•	•	•	•	•
Anti-tip tray system	•	•	•	•	•	•	•

ACCESORIES

MultiCook / cast aluminium tray	optional	optional	optional	optional / -	optional / -	optional / -	optional / -
Anti-tip baking / deep tray (50 mm)	- / •	• / •	- / •	- / •	- / •	- / •	- / •
Anti-tip reinforced / cooking grid	- / •	- / •	- / •	- / •	- / •	- / •	- / •

POWER CONSUMPTION

Turbo, W	-	-	-	-	-	-	-
Grill / Maxi grill, W	1.100/2.500	1.400 / -	1.400 / -	1.400 / -	1.400 / -	1.400 / -	1.400 / -
Traditional, W	2.550	2.550	2.550	2.550	2.550	2.550	2.550
Multifunction motor, W	22	22	22	22	-	-	-
Bottom heat, W	1.150	1.150	1.150	1.150	1.150	1.150	1.150
Cooling fan motor, W	18	18	18	18	18	18	18

ELECTRICAL FEATURES

Voltage, V	220/240	220/240	220/240	220/240	220/240	220/240	220/240
Frequency, HZ	50/60	50/60	50/60	50/60	50/60	50/60	50/60
Maximum connection rating, W	2.615	2.615	2.615	2.615	2.593	2.593	2.593
Cable connection length, cm	110	110	110	110	110	110	110

Model	COMBO 45.15	HL 940	HL 940 WHITE	HS 900	HDL 888	HDL 718
Energy Efficiency Index (EEI) - Main/Top cavity	95,8	98,9	98,9	103,4	106,3/94,1	88,7/107,4
Energy Efficiency Class - Main/Top cavity	A/-	A/-	A/-	A/-	A/A	B/A
Energy consumption per cycle in conventional mode (kWh) - Main/Top cavity	0,7/-	1,10/-	1,10/-	0,7/-	-/0,64	-/0,73
Energy consumption per cycle in fan-forced convection mode (kWh) - Main cavity	0,68	0,86	0,86	0,7	0,84	0,63
Number of cavities	2	1	1	1	2	2
Heat source - Main/Top cavity	Electric	Electric	Electric	Electric	Electric	Electric
Volume (l) - Main/Top cavity	38/18	77 / -	77 / -	77 / -	57 / 31	38 / 31

DIMENSIONS

External, mm	595	480	480	480	888	718
Width, mm	595	890	890	890	595	595
Depth, mm	562	560	560	560	562	562
Inner height, mm	215/117	318	318	318	161/313	161/215
Inner width, mm	452/418	639	639	639	438/455	438/452
Inner depth, mm	395/368	380	380	380	425/396	425/395

CLEANING SYSTEMS

HydroClean®	-	PRO	PRO	ECO	-	-
Easy cleaning enamel	• / -	Slippery	Slippery	Slippery	•	•

FEATURES

Type	Combo Multifunction	Multifunction Turbo	Multifunction Turbo	Multifunction	Multifunction Turbo double oven	Multifunction Turbo double oven
Stainless steel (fingerprint proof)	•	•	White	•	•	•
Cooking functions	5	9	9	7	4 + 4	4 + 1
Touch control digital timer	•	•	•	-	•	•
Analogic timer with stop programmer	-	-	-	-	-	-
Mechanical timer with stop programmer	-	-	-	•	-	-
Telescopic tray guides	- / •	1+1 total	1+1 total	-	-	-
Chromed tray guides	• / -	•	•	•	•	•
MCS Mix Chamber System	-	-	-	-	-	-
Forced refrigeration	Tangential	Tangential	Tangential	Tangential	Tangential	Tangential
Fume scape outlet	Vault/rear	Vault	Vault	Vault	Vault	Vault
Light	25+25	Side 25+25	Side 25+25	25 + 25	25 + 25	25 + 25

SAFETY SYSTEMS

Glazed door	2	3	3	2	2	2
Door opening security disconnection	•	•	•	-	-	-
Children safety	•	•	•	-	•	•
Grill protector	•	•	•	•	•	•
Anti-tip tray system	•	•	•	•	•	•
Safety thermostat	•	•	•	•	•	•

ACCESORIES

Baking tray	1	1	1	-	-	-
Deep tray, 50 mm	1	1	1	1	1 + 1	1
Chromed cooking grid	1	1	1	1	1 + 2	2 + 1
Tray handle	-	-	-	-	1	1

POWER CONSUMPTION

Turbo, W	-	2400	2400	-	0 + 2000	0 + 1800
Grill / Maxi grill, W	1400/1800	1700 / 2750	1700 / 2750	1700/2750	1500/1100	1500/1100
Traditional, W	2450/3600	2755	2755	2755	-	-
Multifunction motor, W	30/-	30	30	30	0 + 27	0 + 27
Bottom heat, W	1050/1800	1055	1055	1055	1050+0	1050+0
Cooling fan motor, W	18	18	18	18	18	18

ELECTRICAL FEATURES

Voltage, V	220-240	220/240	220/240	220/240	220/240	220/240
Frequency, HZ	50/60	50/60	50/60	50/60	50/60	50/60
Maximum connection rating, W	2655-3643	3553	3553	2848	5322	4498
Cable connection length, cm	110	190+plug	190+plug	110	-	-

PRODUCT FICHE ACCORDING TO COMMISSION DELEGATED REGULATION (EU) NO 65/2014

Model	HR 750 AT/BG B/G	HR 650 AT	HR 550 AT/BG B/G	HGR 650 AT/BC B	HGL 924 HGL 824	FGA 820
Energy Efficiency Index (EEI)	101,3	101,3	100	112,88	129,4	112,88
Energy Efficiency Class	A	A	A	B	B	B
Energy consumption per cycle in conventional mode (kWh)	0,83	0,84	0,79	1,73	2,36	1,73
Energy consumption per cycle in fan-forced convection mode (kWh)	0,8	0,8	0,86	1,87	2,54	-
Number of cavities	1	1	1	1	1	1
Heat source	Electric	Electric	Electric	Gas	Gas+electric	Gas
Volume (l)	57	57	57	45	69	45

DIMENSIONS

Height, mm	595	595	595	595	595	595
Width, mm	595	595	595	595	898/798	595
Depth, mm	562	562	562	562	559	562
Inner height, mm	313	313	313	320	308	315
Inner width, mm	455	455	455	419	615	466
Inner depth, mm	396	396	396	395	388	396

CLEANING SYSTEMS

HydroClean®	-	-	-	-	-	-
Easy cleaning enamel	•	•	•	•	•	•

FEATURES

Type	Multifunction Turbo	Multifunction Turbo	Multifunction	MF gas oven + gas Grill	Gas oven + electric grill	Gas oven + electric grill
Stainless steel (fingerprint proof)	Anthracite/Beige / Bright Cream B - brass	Anthracite B - brass	Anthracite/Beige / Bright Cream B - brass	Anthracite B / Bright Cream B - brass	•	•
Cooking functions	9	9	5	4	5	4
Touch control digital timer	-	-	-	-	-	-
Analogic timer with stop programmer	•	•	•	•	-	-
Mechanical timer with stop programmer	-	-	-	-	•	•
Telescopic tray guides	2	1	1	-	-	-
Chromed tray guides	•	•	•	•	•	•
MCS Mix Chamber System	-	-	-	-	-	•
Forced refrigeration	Dinamic	Dinamic	Dinamic	Tangential	Tangential	Tangential
Fume scape outlet	Vault	Vault	Vault	Vault	Vault	Vault
Light	25	25	25	25	25+25	25

SAFETY SYSTEMS

Glazed door	2	2	2	2	3	2
Door opening security disconnection -/	•	-	-	-	-	-
Children safety	-	-	-	-	-	-
Grill protector	•	•	•	-	-	-
Anti-tip tray system	•	•	•	•	•	•
Safety thermostat	•	•	•	•	•	•

ACCESORIES

Baking tray	1	-	-	-	-	-
Deep tray, 50 mm	1	1	1	1	1	1
Chromed cooking grid	1	1	1	1	1	1
Tray handle	-	-	-	-	-	-

POWER CONSUMPTION

Turbo, W	2000	2000	-	27	-	-
Grill / Maxi grill, W	1500 / 2600	1500 / 2600	1400	1800	-	1400
Traditional, W	-	-	-	-	1900	-
Multifunction motor, W	30	30	30	27	30	-
Bottom heat, W	1150	1150	1150	2200	4000	2400
Cooling fan motor, W	18	18	18	18	18	18

ELECTRICAL FEATURES

Voltage, V	220/240	220/240	220/240	220/240	127	220/240
Frequency, HZ	50/60	50/60	50/60	50/60	50/60	50/60
Maximum connection rating, W	2693	3223	2623	70	1998	1447
Cable connection lenght, cm	195+plug	195+plug	195+plug	3 x 0,75	110	110

Model	HGS 924	HGS 824	HGS 930	HGS 740	FGE 724	FGE 730
Energy Efficiency Index (EEI)	129,4	129,4	129,4	112,88	112,88	112,88
Energy Efficiency Class	B	B	B	B	B	B
Energy consumption per cycle in conventional mode (kWh)	2,36	2,36	2,28	1,73	1,73	1,73
Energy consumption per cycle in fan-forced convection mode (kWh)	2,54	2,54	2,48	1,87	-	-
Number of cavities	1	1	1	1	1	1
Heat source	Gas+electric	Gas+electric	Gas	Gas	Gas	Gas
Volume (l)	69	69	64	45	45	45

DIMENSIONS

Height, mm	595	595	595	595	595	595
Width, mm	898	798	898	595	595	595
Depth, mm	549	525	549	562	562	562
Inner height, mm	308	308	280	320	315	315
Inner width, mm	615	615	615	466	466	466
Inner depth, mm	388	388	388	400	390	390

CLEANING SYSTEMS

HydroClean®	-	-	-	-	-	-
Easy cleaning enamel	•	•	•	•	•	•

FEATURES

Type	MF gas oven + electric grill	MF gas oven + electric grill	MF gas oven + gas Grill	MF gas oven + gas grill	Gas oven + electric grill	Gas oven + gas grill
Stainless steel (fingerprint proof)	•	•	•	•	•	•
Cooking functions	5	5	4	4	2	2
Touch control digital timer	-	-	-	-	-	-
Analogic timer with stop programmer	-	-	-	-	-	-
Mechanical timer with stop programmer	•	•	•	•	•	-
Telescopic tray guides	-	-	-	-	-	-
Chromed tray guides	•	•	•	•	•	•
MCS Mix Chamber System	-	-	-	-	•	•
Forced refrigeration	Tangential	Tangential	Tangential	Tangential	Tangential	Tangential
Fume scape outlet	Vault	Vault	Vault	Vault	Vault	Vault
Light	25+25	25+25	25+25	25	25	25

SAFETY SYSTEMS

Glazed door	2	2	2	2	2	2
Door opening security disconnection -/	-	-	-	-	-	-
Children safety	-	-	-	-	-	-
Grill protector	-	-	-	-	-	-
Anti-tip tray system	•	•	•	•	•	•
Safety thermostat	•	•	•	•	•	•

ACCESORIES

Baking tray	-	-	-	-	-	-
Deep tray, 50 mm	1	1	1	1	1	1
Chromed cooking grid	1	1	1	1	1	1
Tray handle	-	-	-	-	-	-

POWER CONSUMPTION

Turbo, W	-	-	-	27	-	-
Grill / Maxi grill, W	2000	-	2500	1800	1400	2000
Traditional, W	-	1900	-	-	-	-
Multifunction motor, W	30	30	30	27	-	-
Bottom heat, W	4000	4000	4000	2200	2400	2400
Cooling fan motor, W	18	18	18	18	18	18

ELECTRICAL FEATURES

Voltage, V	220/240	127	220/240	220/240	220/240	220/240
Frequency, HZ	50/60	50/60	50/60	50/60	50/60	50/60
Maximum connection rating, W	2098	1998	98	70	1443	43
Cable connection lenght, cm	110	110	110	3 x 0,75	110	110