

DEF 9800.0 E

Built-in Slimline cooker hood



EAN / TKI Code

- EAN Code 4037321042033
- TKI Code 123060000

Features

- 6 power levels incl. high power setting
- Extraction rate (to the outside): max. normal power setting 498 m³/h, intensive power setting 706 m³/h
- Telescopic canopy
- Electronic control with push buttons
- LED Display for power levels
- Operated from the right side
- Filter saturation indicator
- Automatic delay stop
- Metal grease filter
- Extendable glass panel to enlarge the catchment area
- Recirculation air mode possible (see optional accessories)
- Front grip panel, stainless steel (changeable)

Technical data

- Electrical connection 272 W
- Exhaust air connection Ø 150 mm
- LED light colour 4,000-4,500 Kelvin


Optional accessories

- Charcoal filter ZD 1011 (2 pieces needed)


Dimensions

- Appliance dimensions W x H x D approx. 898 x 396 x 300 - 455 mm
- Niche dimensions W x H x D approx. 900 x 450 x 300 mm

Drawing



Energy label



Küppersbusch

Product Information Sheet

Delegated Regulation (EU) 65/2014

Supplier name or trademark	Küppersbusch
Model identifier	DEF9800.0E
Annual Energy Consumption	40.1 kWh/annum
Energy Efficiency Class	A+
Fluid Dynamic Efficiency	36.7
Fluid Dynamic Efficiency class	A
Lighting Efficiency	55.7 Lux/W
Lighting Efficiency class	A
Grease Filtering Efficiency	84 %
Grease Filtering Efficiency class	C
Air flow (min speed normal use)	319 m3/h
Air flow (max speed normal use)	523 m3/h
Air flow (intensive or boost use)	740 m3/h
Airborne acoustical A-weighted sound power emissions (min speed normal use)	53 dB
Airborne acoustical A-weighted sound power emissions (max speed normal use)	65 dB
Airborne acoustical A-weighted sound power emissions (intensive or boost use)	70 dB