Depth (mm)	Width (mm)	Height (mm)	Recirculation installation modes	Regenerative charcoal filter (opt)	Removable oil collector	Opening system	Lamps type	Light intensity regulation	Filter saturation indicator	Stop delay timer	Fresh air function	Control panel
325	598	690 - 1035	Only with		•	Suppor			<	<	-	Touch
325	598	690 - 1035	Only with tube cover		-	Support Hinge	LED	-	<	<	-	Touch control
325	869	690 - 1035	Only with		-	Support Hinge	LED		<	~	-	Touch control
325	869	690 - 1035	Only with tube cover		-	t Hinge	Ü		<	V	-	ontrol
325	868	690 - 1035	Only with tube cover	-	-	Support Hinge	LED		<	~	-	Touch control
325	868	690 - 1035	ube cover		-	t Hinge	Ū		<	<	-	sontrol



teka.com

Depth (mm)	Width (mm)	Height (mm)	Recirculation installation modes	Regenerative charcoal filter (opt)	Removable oil collector	Opening system	Lamps type	Light intensity regulation	Filter saturation indicator	Stop delay timer	Fresh air function	Control panel	Dual aspiration system	Aspiration type	Motor type	Air flow (Qmin) m3/h	Air flow (Qmax) m3/h	Air flow (Qboost) m3/h	Number of speeds	Noise level db(A)	Energy efficiency class	MODEL	ТЕКА
450	600	1001 - 1331	With or withc	~	<	Pist	LED BAR	-	<	<	~	Touch contro	-	Rim ext	Brushless	200	600	880	3+1	39	A+++	DLV 69670 TOS BK	
450	006	1001 - 1331	With or without tube cover	~	~	Piston	BAR	-	~	~	V	Touch control with display		Rim extraction	nless	210	625	920	3+1	39	A+++	DLV 99670 TOS BK	
450	600	1001 - 1331	With or without tube cover	~	~	Piston	LED BAR		~	V	~	Touch control with display	•	Rim extraction	Ecop	232	410	725	3+1	49	A+	DLV 68660 TOS BK/WH	
450	006	1001 - 1331	ut tube cover	<	~	ion	BAR	-	~	~	~	l with display		raction	Ecopower	290	558	969	3+1	51	T	DLV 98660 TOS BK/WH	
412	600	800 - 1100		~	<				<	~	~		<		Ecop	307	584	869	3+1	61		DVT PRO 68660 TBS BK/WH	
412	700	800 - 1100	With	<	<	_			<	<	~	Touch	<	-	Ecopower	307	584	869	3+1	61	A+	DVT PRO 68660 DVT PRO 78660 DV TBS BK/WH TBS BK/WH 1	
424	700	800 - 1100	With or without tube cover	<	<	Piston	LED		~	~	~	Touch control with display	~	Rim extraction	Brushless	237	381	678	3+1	52,6	A+++	DVT PRO 78780 TCS BK/WH	
412	006	800 - 1100	cover	~	<	_			~	~	~	lisplay	~		Ecopower	307	584	869	3+1	61	A+	ГГ PRO 78780 DVT PRO 98660 DVT PRO 98780 ГСЅ ВК/WH ТВЅ ВК/WH TCЅ ВК/WH	
424	006	800 - 1100		~	<	_		-	~	~	~	_	~		Brushless	237	381	678	3+1	52,6	A+++	DVT PRO 98780 TCS BK/WH	
325	598	690 - 1035	Onl							~						380	410	425	2+1	65		DVN 64030 TTC BK/WH	4 1
325	869	690 - 1035	Only with tube cover			Support hinge	LED			<	•	Touch control		Rim extraction	Double Turbine	380	410	425	2+1	65	C	DVN 74030 TTC BK/WH	
325	868	690 - 1035	ver							<			•			380	410	425	2+1	65		DVN 94030 TTC BK/WH	(





NEW RANGE OF VERTICAL HOODS Art in your kitchen



CUTTING EDGE DESIGN

Minimalist design with a glass finish that gives a touch of functional exclusivity to your kitchen.

Its lines create an exclusive style, integrating into the environment in a clean and uniform way.

This new design will make you enjoy not only its exceptional functions, but a modern and pleasant space in your kitchen.

MORE VERSATILE

Installation with or without coverings. With recirculation or with outside extraction.

All the options you need in this wide range, where each model integrates into your kitchen like a small piece of art. Additionally, DVT models include a drilling guide for the wall, and parts pre-assembled from the factory, for a much easier and faster installation.



A BREATH OF FRESH AIR IN YOUR KITCHEN

TEKA



Renovate the air in your kitchen with the Fresh Air function for a clean and fresh environment.

It renews air for 24 hours in cycles of 10 minutes per hour. An ideal function for meetings at home, as it allows you to get rid of annoying odours, always keeping your home fresh.

Your home free of odours with the new latest generation regenerative* filters. Eliminates up to 95% of odours for approximately three years.

*Optional filters for recirculation installation.

LATEST GENERATION MOTORS

More Silence, more extraction and with minimal consumption.

More efficient motors, which provide energy savings, greater durability and less noise.

The **extra silent Brushless motor** gives us minimum noise levels of up to 39db, equivalent to the noise of a whispered conversation. Moreover, these extra silent motors provide high durability thanks to their robust design.

The addition of an extra filter improves the extraction and odour removal, by combining front and perimeter extraction with the **Dual Aspiration System.**



With energy ratings up to A +++.

Meeting the energy criteria for Passive House homes, our hoods allow recirculating installation, avoiding the need for air vents to the outside which favours the isolation method. In this way, it is possible to reduce the energy needed for the air conditioning in your home.

Efficiency and savings guarantee with LED lighting. Light right where you need it with **adjustment lamps** directly in the cooking area. You can also **adjust the intensity** of the light as you like.





EASY USE AND CLEANING

Access your hood filters in the easiest way for a quick and easy clean.

Thanks to the pistons, the glass remains open, thus improving security while cleaning.

Get impeccable cleaning results with the additional removable tray. It's as easy as taking it out and putting it in the dishwasher for a deep clean.

The control panel is fully integrated into the glass, so, in addition to an intuitive design, it makes it easier to clean.