AKDO®

BOOST STONE

Porcelain

Modern. Minimalist. Sleek.
A standout surface with rugged sophistication.



Far Beyond the Surface

Only sold in CT, GA, ME, MA, NH, NJ, NY, PA, RI, and VT

Boost Stone 12″ x 24″ Clay (M)

PO2699-1224M0

Boost Stone 24″ x 24″ Clay (M)

PO2699-2424M0

Boost Stone 24″ x 48″ Clay (M)

PO2699-2448M0

Product shown on cover: Boost Stone 24″ x 48″ White (M)

Boost Stone 2″ x 2″ Clay (M)

PO2699-MOSCM0

Boost Stone Hexagon Mosaic Clay (M)

PO2699-M0HEX0

Boost Stone Brick Mosaic Clay (M)

PO2699-1224BR

Product shown: Boost Stone Clay (M)

BOOST STONE

Cream

Only sold in CT, GA, ME, MA, NH, NJ, NY, PA, RI, and VT

Boost Stone 12″ x 24″ Cream (M)

PO2700-1224M0

Boost Stone 24″ x 24″ Cream (M)

PO2700-2424M0

Boost Stone 24″ x 48″ Cream (M)

PO2700-2448M0

Boost Stone 2″ x 2″ Cream (M)

PO2700-M0SCM0

Boost Stone Hexagon Mosaic Cream (M)

PO2700-M0HEX0

Boost Stone Brick Mosaic Cream (M)

PO2700-1224BR

Only sold in CT, GA, ME, MA, NH, NJ, NY, PA, RI, and VT

Boost Stone 12″ x 24″ Pearl (M)

PO2693-1224M0

Boost Stone 24″ x 24″ Pearl (M)

PO2693-2424M0

Boost Stone 24″ x 48″ Pearl (M)

PO2693-2448M0

Boost Stone 2″ x 2″ Pearl (M)

PO2693-MOSCM0

Boost Stone Hexagon Mosaic Pearl (M)

PO2693-M0HEX0

Boost Stone Brick Mosaic Pearl (M)

PO2693-1224BR

Product shown: Boost Stone Hexagon Mosaic Pearl (M)

Only sold in CT, GA, ME, MA, NH, NJ, NY, PA, RI, and VT

Boost Stone 12″ x 24″ Smoke (M)

PO2695-1224M0

Boost Stone 24″ x 24″ Smoke (M)

PO2695-2424M0

Boost Stone 24″ x 48″ Smoke (M)

PO2695-2448M0

Boost Stone 2″ x 2″ Smoke (M)

PO2695-MOSCM0

Boost Stone Hexagon Mosaic Smoke (M)

PO2695-M0HEX0

Boost Stone Brick Mosaic Smoke (M)

PO2695-1224BR

Only sold in CT, GA, ME, MA, NH, NJ, NY, PA, RI, and VT

Boost Stone 12″ x 24″ Tarmac (M)

PO2697-1224M0

Boost Stone 24″ x 24″ Tarmac (M)

PO2697-2424M0

Boost Stone 24″ x 48″ Tarmac (M)

PO2697-2448M0

Boost Stone 2″ x 2″ Tarmac (M)

PO2697-MOSCM0

Boost Stone Hexagon Mosaic Tarmac (M)

PO2697-M0HEX0

Boost Stone Brick Mosaic Tarmac (M)

PO2697-1224BR

Product shown: Wall - Boost Stone Smoke (M), Floor - Boost Stone Tarmac (M)

IT'S NOT HOW GOOD YOU ARE, IT'S HOW GOOD YOU WANT TO BE.

Only sold in CT, GA, ME, MA, NH, NJ, NY, PA, RI, and VT

Boost Stone 12″ x 24″ White (M)

PO2701-1224M0

Boost Stone 24″ x 24″ White (M)

PO2701-2424M0

Boost Stone 24″ x 48″ White (M)

PO2701-2448M0

Boost Stone 2″ x 2″ White (M)

PO2701-MOSCM0

Boost Stone Hexagon Mosaic White (M)

PO2701-M0HEX0

Boost Stone Brick Mosaic White (M)

PO2701-1224BR

Special Order

Boost Stone Cube Mosaic Cold (M)

PO2702-MOCUB0

Special Order

Boost Stone Cube Mosaic Warm (M)

PO2703-MOCUB0

Product shown: Boost Stone Cube Mosaic Cold (M)

Product shown: Boost Stone 24″ x 48″ White (M)

CONVERSION CHART

PROFILE	SIZE
12″ x 24″	11 ¾" x 23 5/8" =1.94 sqft
24″ x 24″	23 5/8" x 23 5/8" = 3.88 sqft
24″ x 48″	23 5/8" x 47 ¼" = 7.75 sqft
2″ x 2″	11 ¾" x 11 ¾" = 0.97 sqft
Brick Mosaic	11 ¾" x 23 5/8" = 1.94 sqft
Hexagon Mosaic	9 7/8" x 11 ¼" = 0.78 sqft
Cube Mosaic	11 ¾" x 11 ¾" = 0.97 sqft

MOSAIC LAYOUT DIMENSIONS



A: 3 7/8″ x 1½″
B: 1 7/8″ x 1½″
C: 1¾″ x 1⅜″



1 7/8″ x 1 7/8″



A: 1½″ x 23 5/8″
B: 5/8″ x 23 5/8″
C: 1¾″ x 23 5/8″

APPLICATIONS

WALL	FLOOR	TRAFFIC	INTERIOR	EXTERIOR FREEZE/THAW	STEAM SHOWER	WET AREA	POOL	BACKSPLASH	FIREPLACE SURROUND
Yes	Yes	Heavy Commercial	Yes	Yes	Yes	Yes	Yes	Yes	Yes

TECHNICAL DATA

FEATURES	STANDARD TEST	SPECIFICATION
Barefoot Ramp Test	DIN 51097	A+B
Bending Resistance	ISO 10545-4	R ≥40 N/mm2
Bond Strength	EN 1348	≥1.0 N/mm2 (Class C2 - EN 12004)
Booted Ramp Test	DIN 51130	R10
Breaking Strength	ISO 10545-4	S ≥1500 N
Coefficient of Friction	B.C.R.A. Rep. CEC/81	>0.40 Dry, >0.40 Wet
Coefficient of Linear Thermal Expansion	ISO 10545-8	≤7MK-1
Dynamic Coefficient of Friction (DCOF)	ANSI A.137.1	> 0.42 Wet
Deep Abrasion Resistance of Unglazed Tiles	ISO 10545-6	≤150mm3
Frost Resistance	ISO 10545-12	Resistant
Impact Resistance	ISO 10545-5	≥0.55
Mohs Hardness		MOHS 6
Moisture Expansion	ISO 10545-10	≤0.01% (0.1mm/m)
Pendulum Friction Test	BS 7976	≥36Dry, ≥36Wet
Pendulum Friction Test	AS 4586	Class P3
Pendulum Friction Test	UNE-ENV 12633 UNE 41901:2017 EX	Class C2
Reaction to Fire		A1 - A1fl
Regularity of Length & Width	ISO 10545-2	Compliant
Regularity of Rectangularity	ISO 10545-2	Compliant
Regularity of Straightness of Sides	ISO 10545-2	Compliant
Regularity of Surface Flatness	ISO 10545-2	Compliant
Regularity of Thickness	ISO 10545-2	Compliant
Resistance to High Concentrations of Acids and Alkalis	ISO 10545-13	HA
Resistance to Household Chemicals	ISO 10545-13	A
Resistance to Low Concentrations of Acids and Alkalis	ISO 10545-13	LA
Resistance to Swimming Pool Salts	ISO 10545-13	A
Stain Resistance	ISO 10545-14	5
Thermal Shock Resistance	ISO 10545-9	Resistant
Water Absorption	ISO 10545-3	≤0.1%
Water Absorption	ASTM C373-18	≤0.5%

Due to the inherent characteristics of porcelain, there may be variations in color, movement and texture from lot to lot.
For detailed installation guidelines, visit akdo.com.

AKDO

1435 State Street
Bridgeport, CT 06605
1.800.811.2536
203.336.5199 (o)
203.336.0603 (f)

AKDO NYC

22 West 21st Street
New York, NY 10010
1.800.811.2536
212.485.0448 (o)
212.485.0449 (f)

AKDO Pacific

3445 Arden Road
Hayward, CA 94545
1.888.909.2536
510.785.2536 (o)
510.785.0895 (f)

akdo.com

COMMERCIAL · HOSPITALITY · RESIDENTIAL

AKDO®