

# SPS HOME

Off-line APFC multi-socket UPS 650 VA and 850 VA



## SPS HOME: Ideal multi-socket solution for office or home environments

Salicru's **SPS HOME** series UPSs boast off-line technology, are available in 650 and 850 VA powers, feature a 6-socket design and have the capacity to protect loads with active power factor correction (APFC).

All of the 6 sockets feature overvoltage protection and 3 or 4 of them have autonomy backup for power failure situations. All of them are also conveniently orientated for easy connection of power supply transformers and are shuttered for child protection. To complete the protection, they also feature RJ45 sockets to protect telephone/ADSL/Ethernet connections from overvoltages and/or electrical noise.

And to facilitate the management and control of the UPS, the USB interface incorporates the HID protocol, which allows the configuration of parameters and the closing/hibernation of the PC. There is also the option of software packages for the monitoring and orderly closing of files for Windows, Linux and Mac.

## Applications: Multiple protection against overvoltages and with backup reserve

In the event of electrical disturbances –outages, micro-cuts, overvoltages and voltage spikes– as a result of various causes – storms, lightning, excessive demand and natural disasters– the best protection for all computer users who depend on a stable and correct power supply in a UPS. Salicru's **SPS HOME** series is, thanks to its multiple sockets, the ideal protection for single-user systems and all of their associated peripherals (HDD, monitor, printer (\*), NAS, router/modem/switch, etc.).

(\* ) Laser printers must only be connected to the overvoltage protection sockets (surge protector).




**SALICRU**

## Performances

- Off-line technology.
- Multiple base design with 6 sockets.
- 3 or 4 sockets with UPS protection; all sockets with over-voltage protection.
- Orientated sockets for easy connection.
- USB interface with HID protocol.
- Downloadable software for Windows, Linux and Mac.
- Telephone line/ADSL + Ethernet network protection 10/100 Mb.
- User-replaceable battery, battery swap function.
- Automatic restart after mains outage or end of backup.
- Cold-start function.
- Backlit On/Off button.
- Auto-detection of operating frequency (50/60 Hz).
- Economic guarantee for connected units up to €70,000. <sup>(1)</sup>

(1) Only European Union countries




## Socket formats available | USB interface with HID protocol

The **SPS HOME** series is available in two different socket versions. The sockets are directly moulded into the top part of the UPS. The popular Schuko version conforms to the German DIN 49440-1 standard used by the majority of European countries and is also compatible with the standard aviation plugs used in France. The BS version is compatible with the plugs used in the UK and Ireland, among other locations.


- Parameter configuration, UPS control and computer shutdown/hibernation through the USB port.
- Available for Windows, Linux and Mac environments.



SCHUKO




U.K.



## Software

UPS monitoring and management software for closing files and applications. Compatible with Windows, Linux and Mac.



## Compatibility with APFC loads

The vast majority of power supplies for electronic devices are switched-mode (SMPS) and they are increasingly being equipped with active power factor correction (APFC) to minimise distortion caused to the electrical line. **SPS HOME** UPSs are compatible with all devices that incorporate these functionalities.



## Range

MODEL SCHUKO	CODE	POWER (VA / W)	NO. OF SOCKETS	DIMENSIONS (D × W × H mm)	WEIGHT (Kg)
SPS 650 HOME	693CA000001	650 / 360	6 (4 UPS + 2 Prot.)	316 × 121 × 94	2.7
SPS 850 HOME	693CA000002	850 / 490	6 (4 UPS + 2 Prot.)	316 × 121 × 94	3

MODEL UK	CODE	POWER (VA / W)	NO. OF SOCKETS	DIMENSIONS (D × W × H mm)	WEIGHT (Kg)
SPS 650 HOME UK	693CA000003	650 / 360	6 (3 UPS + 3 Prot.)	316 × 121 × 94	2.7
SPS 850 HOME UK	693CA000004	850 / 490	6 (3 UPS + 3 Prot.)	316 × 121 × 94	3

## Dimensions




SPS 650/850 HOME UK




SPS 650/850 HOME

## Connections



SPS 650/850 HOME



SPS 650/850 HOME UK

1. UPS backup + overvoltage protection sockets.
2. Overvoltage protection sockets.
3. On/Off button.
4. AC input.
5. USB-HID interface.
6. RJ45 telephone/ADSL/Ethernet protection.
7. Resettable protection circuit breaker.
8. Replaceable battery, battery swap.

## Technical specifications

MODEL		SPS HOME
TECHNOLOGY		Off-line
FORMAT		Socket design
INPUT	Rated voltage	230 V
	Voltage range	180 ÷ 270 V
	Rated frequency	50 / 60 Hz (auto-detection)
	Protection	Resettable breaker
OUTPUT	Rated voltage	230 V
	Voltage accuracy (battery mode)	±7%
	Waveform (battery mode)	Pseudo sine wave
	Frequency	50/60 Hz (same as input)
	Frequency accuracy (battery mode)	±1Hz
	Transfer time	4 ms (typical)
	Compatibility with APFC loads	Yes
BATTERY	Battery type	Pb-Ca sealed, AGM, maintenance-free
	Recharge time	8 hours to 90%
	User replaceable battery	Yes
COMMUNICATION	Ports	USB (HID protocol)
	Monitoring software	For Windows, Linux and Mac
INDICATIONS	Type	LED
	Audible	Every 30 s for battery operation / Every 0.5 s for overload / Continuous for failure
OTHER FUNCTIONS	Self-charge	Yes, even with the device switched off
	Cold start (start-up from batteries)	Yes
	Automatic restart	Yes, after end of backup
	ADSL/fax/modem transient protector	Yes, 2 × RJ45 for tel/fax, Internet ADSL + Ethernet network 10/100 Mb
GENERAL	Operating temperature	0° C ÷ 40° C
	Relative humidity	Up to 95%, non-condensing
	Maximum operating altitude	2,400 masl
	Acoustic noise at 1 metre	<40 dB
STANDARDS	Safety	EN-IEC 62040-1
	Electromagnetic compatibility (EMC)	EN 62040-2
	Operation	EN 62040-3
	Corporate certification	ISO 9001, ISO 14001, ISO 45001

Information subject to change without notice.

