

# ATTESTATION OF CONFORMITY



Issued to: SALICRU S.A.  
Avinguda de la Serra, 100  
08460 Santa Maria de Palautordera, Barcelona, Spain

For the product: Surge Protective Devices

Trade name: SALICRU

Type/Model: 350J and 600J

Ratings: Test class III/Type 3; IP20;  
See further information on Annex

Manufactured by: SALICRU S.A.  
Avinguda de la Serra, 100  
08460 Santa Maria de Palautordera, Barcelona, Spain

Subject: Complete evaluation of electrical system of the appliances

Requirements: EN 61643-11:2012+A11:2018

This Attestation is granted on account of an examination by DEKRA, the results of which are laid down in a test file / test report no. 6218407.50.

This Attestation implies that the examined types are in accordance with the standards designated under the Low Voltage Directive (LVD) 2014/35/EU.

The examination has been carried out on one single specimen or several specimens of the product, submitted by the manufacturer. The Attestation does not include an assessment of the manufacturer's production. Conformity of this production with the specimen tested by DEKRA is not the responsibility of DEKRA.

This document does not authorize the use of any DEKRA approved mark.

Arnhem, 30 May 2025

Number: 6218407.01AOC

DEKRA Testing and Certification (Shanghai) Ltd.

Kate Xu  
Certification Manager

© Integral publication of this attestation and adjoining reports is allowed

DEKRA Testing and Certification (Shanghai) Ltd.  
5F #250 Jiangchangsan Road Shibei Hi-Tech Park, 200436 Jing'an District, Shanghai, China  
T +86 21 6056 7666 F +86 21 6056 7555 [www.dekra-product-safety.com](http://www.dekra-product-safety.com)

# Annex



Document no. : 6218407.01AOC

## Product data

Product	: Surge Protective Devices
Trade name(s)	: SALICRU
Type(s)/model(s)	: 350J and 600J
Number of port(s)	: One
SPD type (Test class)	: Type 3 (III)
Maximum continuous operating voltage (U <sub>c</sub> )	: 320 V~
Open circuit voltage for Type 3 (III) (U <sub>oc</sub> )	: 6 kV (For model 350J); 10 kV (For model 600J)
Voltage protection level (U <sub>p</sub> )	: 1.5 kV
Short-circuit current rating (Isccr)	: 1.5 kA
Modes of protection	: L-N
Degree of protection	: IP20

---

End