Product Spec Sheet


Gavle 6 Dimming Type


Pendant luminaires

Project :	Location :	Type :	Quantity :
Note :			

IP20







Luminaire Structure

Comprehensive range of clean-edged interior circular ring fixtures
Powerful and technical performance options shrouded in a minimalist aesthetic form

Ordering guide sample

GAV-90301 - O - W30 - DA - A80981

Diffuser | Colour | Dim Type | Accessory 1

Diffuser for light output control
O – Opal diffuser UGR <19

Dimming Type
ND – Non dimmable
DI – 1-10V dimmable
DA – DALI dimmable

Colour Temperature
W27 – Warm 2700K
W30 – Warm white 3000K
W40 – Neutral white 4000K
W50 – Cool white 5000K

Product Code

Model No.	No. LED UP	No. LED DOWN	System Power W	Lumen lm	Colour	EEC	Dimension L	Remote Driver	Weight kg
PENDANT · DIRECT - INDIRECT · 100x100MM. · DIMMING TYPE									
GAV-90301* - O - W27	288 LED	288 LED	74	7913	2700K	A++	500	–	6.1
GAV-90301* - O - W30	288 LED	288 LED	74	8276	3000K	A++	500	–	6.1
GAV-90301* - O - W40	288 LED	288 LED	74	8639	4000K	A++	500	–	6.1
GAV-90301* - O - W50	288 LED	288 LED	74	8998	5000K	A++	500	–	6.1
GAV-90311* - O - W27	672 LED	672 LED	172	18653	2700K	A++	1000	–	12.2
GAV-90311* - O - W30	672 LED	672 LED	172	19508	3000K	A++	1000	–	12.2
GAV-90311* - O - W40	672 LED	672 LED	172	20363	4000K	A++	1000	–	12.2
GAV-90311* - O - W50	672 LED	672 LED	172	21210	5000K	A++	1000	–	12.2
GAV-90321* - O - W27	960 LED	960 LED	244	27840	2700K	A++	1500	–	17.8
GAV-90321* - O - W30	960 LED	960 LED	244	29116	3000K	A++	1500	–	17.8
GAV-90321* - O - W40	960 LED	960 LED	244	30393	4000K	A++	1500	–	17.8
GAV-90321* - O - W50	960 LED	960 LED	244	31657	5000K	A++	1500	–	17.8
GAV-90331* - O - W27	1344 LED	1344 LED	346	38783	2700K	A++	2000	–	23.2
GAV-90331* - O - W30	1344 LED	1344 LED	346	40562	3000K	A++	2000	–	23.2
GAV-90331* - O - W40	1344 LED	1344 LED	346	42340	4000K	A++	2000	–	23.2
GAV-90331* - O - W50	1344 LED	1344 LED	346	44101	5000K	A++	2000	–	23.2
GAV-90341* - O - W27	1728 LED	1728 LED	458	50673	2700K	A++	2500	–	31.8
GAV-90341* - O - W30	1728 LED	1728 LED	458	52997	3000K	A++	2500	–	31.8
GAV-90341* - O - W40	1728 LED	1728 LED	458	55320	4000K	A++	2500	–	31.8
GAV-90341* - O - W50	1728 LED	1728 LED	458	57621	5000K	A++	2500	–	31.8
GAV-90351* - O - W27	1920 LED	1920 LED	505	54962	2700K	A++	3000	–	38.2
GAV-90351* - O - W30	1920 LED	1920 LED	505	57482	3000K	A++	3000	–	38.2
GAV-90351* - O - W40	1920 LED	1920 LED	505	60002	4000K	A++	3000	–	38.2
GAV-90351* - O - W50	1920 LED	1920 LED	505	62498	5000K	A++	3000	–	38.2
GAV-90361* - O - W27	2688 LED	2688 LED	690	76946	2700K	A++	4000	–	50.1
GAV-90361* - O - W30	2688 LED	2688 LED	690	80474	3000K	A++	4000	–	50.1
GAV-90361* - O - W40	2688 LED	2688 LED	690	84002	4000K	A++	4000	–	50.1
GAV-90361* - O - W50	2688 LED	2688 LED	690	87496	5000K	A++	4000	–	50.1
GAV-90371* - O - W27	3456 LED	3456 LED	915	101112	2700K	A++	5000	–	60.2
GAV-90371* - O - W30	3456 LED	3456 LED	915	105748	3000K	A++	5000	–	60.2
GAV-90371* - O - W40	3456 LED	3456 LED	915	110384	4000K	A++	5000	–	60.2
GAV-90371* - O - W50	3456 LED	3456 LED	915	114976	5000K	A++	5000	–	60.2

*For Remote driver is included. (DI – 1-10V dimmable)

Light Symbol



Indirect pendant light

HEADQUARTERS EUROPE

Ligman Europe s.r.o.
VGP Park Ústí nad Labem, P2 | Přestanov 120 | 40317 Přestanov | Czech Republic | Tel. +420 477 07 1500 | sales.cz@ligman.com

www.ligman.com

HEADQUARTERS THAILAND

Ligman Lighting Co.,Ltd.
17/2 | Moo 4 | Monthong | Bangnampreaw | Chachoengsao 24150 | Thailand | Tel : +66 (2) 7339140 | info@ligman.com

Ligman Ltd.
Victory Way | Crossways | Dartford DA2 6QD |
United Kingdom | Tel +66 2 733 9140 | Fax +66 2 733 9153 |
sales.uk@ligman.com

Technical amendments reserved.


Product Spec Sheet

Gavle 6 Dimming Type

Pendant luminaires


Project :	Location :	Type :	Quantity :
Note :			

Len diffuser



☐ (- O)
Opal diffuser
UGR <19

Accessory



☐ Surface Mounted For Supply Cable
(A80981)


Dimming Type

☐ ND ☐ DI ☐ DA

Accessory For Wireless Bluetooth



☐ Wireless Bluetooth
(A90291)



☐ xPress Wireless switch
(A90591)


Colour Code


☐ - 01 ☐ - 03 ☐ - 05


Black RAL 9011 | White RAL 9003 | Matt Silver RAL 9006


RESET


Photometric




















• Installation manual available online at www.ligman.com.
• Luminous flux and system power are rated from absolute photometry according to LM-79-08 standard for LED luminaire.
• Photometric diagram for standard non-accessory, please consult the factory in case accessory option.

HEADQUARTERS EUROPE

Ligman Europe s.r.o.
VGP Park Ústí nad Labem, P2 | Přestanov 120 | 40317 Přestanov | Czech Republic | Tel. +420 477 07 1500 | sales.cz@ligman.com

www.ligman.com

HEADQUARTERS THAILAND

Ligman Lighting Co.,Ltd.
17/2 | Moo 4 | Monthong | Bangnampreaw | Chachoengsao 24150 | Thailand | Tel : +66 (2) 7339140 | info@ligman.com

Ligman Ltd.
Victory Way | Crossways | Dartford DA2 6QD |
United Kingdom | Tel +66 2 733 9140 | Fax +66 2 733 9153 |
sales.uk@ligman.com

Technical amendments reserved.