


**360° Lighting (54 W)** (LCO-20011)

microVOS

LIGHT  
CONNECT™**Luminaire Structure**

- Die-cast aluminium housing
- Pre-treated before powder coating ensuring high corrosion resistance
- Single cable entry
- Stainless steel fasteners in grade 304 with zinc flake coating (ZFC)
- Durable silicone rubber gasket
- High-efficiency PMMA lens
- Clear acrylic PMMA diffuser

**Optic**

**360° Lighting (54 W) (LCO-20011)**

**Technical information**

<b>Light source</b>	28 LED	<b>Optic value</b>	94°, 142° x 58°, 131° x 56°, 123°	<b>Weight</b>	14.8 kg
<b>Power</b>	54 W	<b>CCT / CRI</b>	3000K, 4000K	<b>EPA (m2)</b>	0.170
<b>Lumen</b>	4574 - 5658 lm	<b>Bug</b>	B1-U2-G1, B1-U3-G1, B2-U3-G1, B3-U2-G3	<b>Through wiring</b>	Single cable entry
<b>Efficacy</b>	85 - 105 lm/W	<b>ULR</b>	1%, 2%	<b>Lens / Reflector / Optic</b>	High-efficiency PMMA lens, Clear acrylic PMMA diffuser
<b>Input voltage</b>	220-240V 50/60Hz	<b>ULOR</b>	1%, 2%	<b>VARIANTS</b>	Compatible with EN/ IEC 60598-2-22: Suitable for emergency installations as central supply, non-maintained (Z0)
<b>Optic</b>	W, T2, T3, T5	<b>CIE flux code n°3</b>	95, 96, 98		

LCO-20011

