


360° Lighting (54 W) + WiFi 6 AX (LCO-20012)

microVOS

LIGHT
CONNECT™**Luminaire Structure**

- Die-cast aluminium housing
- Pre-treated before powder coating ensuring high corrosion resistance
- Single cable entry
- Stainless steel fasteners in grade 304 with zinc flake coating (ZFC)
- Durable silicone rubber gasket
- High-efficiency PMMA lens
- Clear acrylic PMMA diffuser

Optic

360° Lighting (54 W) + WiFi 6 AX (LCO-20012)

Technical information

Light source	28 LED	Optic value	94°, 142° x 58°, 131° x 56°, 123°	Weight	15.9 kg
Power	54 W	CCT / CRI	3000K, 4000K	EPA (m2)	0.170
Lumen	4574 - 5658 lm	Bug	B1-U2-G1, B1-U3-G1, B2-U3-G1, B3-U2-G3	Through wiring	Single cable entry
Efficacy	85 - 105 lm/W	ULR	1%, 2%	Lens / Reflector / Optic	High-efficiency PMMA lens, Clear acrylic PMMA diffuser
Input voltage	220-240V 50/60Hz	ULOR	1%, 2%	VARIANTS	Compatible with EN/ IEC 60598-2-22: Suitable for emergency installations as central supply, non-maintained (Z0)
Optic	W, T2, T3, T5	CIE flux code n°3	95, 96, 98		

LCO-20012

