

SANDY 4 (SA-31501-1MS)



Product description

Small - With integrated motion sensor




microPrim™



Luminaire Structure

- Die-cast aluminium housing and frame
- Pre-treated before powder coating ensuring high corrosion resistance
- Two cable entries for through wiring
- Stainless steel fasteners in grade 304 with zinc flake coating (ZFC)
- Durable silicone rubber gasket
- Opal UV-stabilised polycarbonate diffuser
- Integral control gear
- Optional surface mounting box for easy wiring or conduit connection when wiring from behind is not possible

Optic




G

Product colour



Special finishes upon request



SANDY 4 (SA-31501-1MS)



Technical information

Material	Aluminium
Light source	80 LED
Power	19 W
Lumen	873 - 920 lm
Efficacy	46 - 48 lm/W
Driver option	Integral control gear
Driver	Constant current (CC)
Input voltage	220-240 V 50/60 Hz

Optic	G
Optic value	107°x107°
CCT / CRI	3000K CRI80, 4000K CRI80
Bug	B0-U3-G2
ULR	36
ULOR	36
CIE flux code n°3	73
Dimming type	On/Off, 1-10V

Product colours	Black, Dark Grey, White, Matt Silver, Bronze, Concrete - Urban, Softscape - Urban, Stone - Urban, Corten - Urban, Oak - Woodland, Walnut - Woodland, Pine - Woodland
Weight	2.3 kg
Through wiring	Two cable entries for through wiring
Lens / Reflector / Optic	Opal UV-stabilised polycarbonate diffuser
MacAdam Ellipse	3 SDCM
Lifetime L90B10 (hours)	> 37,000
Lifetime L80B10 (hours)	> 78,000
Lifetime L80B50 (hours)	> 86,000

SA-31501-1MS



- SANDY**
- Blue sensor - Microsensor - 1-10V**
Adjustable sensor (10 seconds - 10 minutes)
10° Sensibility
Sensor detection area:
SA-3148-1MS, SA-3152-1MS, SA-3153-1MS (L 2° - 4.8 m)
SA-3148-1MS, SA-3152-1MS (L 3° - 7.0 m)
SA-3149-1MS, SA-3151-1MS, SA-3152-1MS, SA-3153-1MS (L 3° - 4.5 m)
 - Red sensor - Microsensor - On/Off**
Adjustable sensor (8 seconds - 30 minutes)
10° Sensibility
Sensor detection area:
SA-3151-1MS, SA-3152-1MS, SA-3153-1MS (L 2° - 4.8 m)
SA-3148-1MS, SA-3152-1MS (L 3° - 7.0 m)
SA-3149-1MS, SA-3151-1MS, SA-3152-1MS, SA-3153-1MS (L 3° - 4.5 m)

SANDY 4 (SA-31501-1MS)**Accessory**



Surface mounting box for easy
cabling (SANDY 4)
SCE-SANDY-4



DALI Control System
Control-DALI



Remote controller for the motion
sensor - 1-10V (A34191)
A34391
