

**POWERMISSION 3 (PO39-LM162)**




**Luminaire Structure**

- Die-cast aluminium housing
- Pre-treated before powder coating ensuring high corrosion resistance
- Thermal heat dissipation body

- Stainless steel fasteners in grade 304 with zinc flake coating (ZFC)
- Durable silicone rubber gasket
- Clear toughened glass


- Integral control gear
- Surge protection 10kV

**Optic**




T2 T3 T4 ME

**Product colour**



01 - Black (RAL 9011)    02 - Dark Grey (RAL 7043)    03 - White (RAL 9003)    05 - Matt Silver (RAL 9006)  
06 - Bronze (RAL 6014)

**Special finishes upon request**



SU01 - Concrete - Urban    SU02 - Softscape - Urban    SU03 - Stone - Urban    SU04 - Corten - Urban  
SW01 - Oak - Woodland    SW02 - Walnut - Woodland    SW03 - Pine - Woodland

**POWERMISSION 3 (PO39-LM162)**
**Technical information**

<b>Material</b>	Aluminium	<b>Driver</b>	Constant current (CC)	<b>Product colours</b>	Black, Dark Grey, White, Matt Silver, Bronze, Concrete - Urban, Softscape - Urban, Stone - Urban, Corten - Urban, Oak - Woodland, Walnut - Woodland, Pine - Woodland
<b>Light source</b>	48 LED	<b>Input voltage</b>	220-240 V 50/60 Hz	<b>Weight</b>	10.6 kg
<b>Power</b>	154 W	<b>Optic</b>	T2, T3, T4, ME	<b>Operating temperature</b>	-20 °C to 40 °C
<b>Lumen</b>	15062 - 16827 lm	<b>Optic value</b>	145°x54°, 138°x73°, 96°x75°, 140°x58°	<b>Lens / Reflector / Optic</b>	Clear toughened glass
<b>Efficacy</b>	193 - 216 lm/W	<b>CCT / CRI</b>	3000K CRI80, 4000K CRI80	<b>Variants (On/Off, DALI)</b>	Compatible with EN/ IEC 60598-2-22: Suitable for emergency installations as central supply, non-maintained (Z0)
<b>Driver option</b>	Integral control gear	<b>Dimming type</b>	On/Off, 1-10V, DALI		