


**TUSCON 2 (TS-80031)****Product description**

147x579 mm

**Luminaire Structure**

- Die-cast aluminium housing with powder coating
- Die-cast aluminium heat sink with excellent thermal management
- Adjustable: Tilt 30°
- Proprietary lens design for high LOR
- Remote driver (included)

**Optic****Product colour**

**TUSCON 2 (TS-80031)**

**Technical information**

<b>Material</b>	Aluminium
<b>Light source</b>	12 LED
<b>Power</b>	79 W
<b>Lumen</b>	6048 - 6880 lm
<b>Efficacy</b>	76 - 86 lm/W
<b>Driver option</b>	Remote driver (included)
<b>Driver</b>	Constant current (CC)

<b>Input voltage</b>	220-240 V 50/60 Hz
<b>Optic</b>	N, M, W
<b>Optic value</b>	15°, 26°, 39°
<b>CCT / CRI</b>	3000K CRI80, 4000K CRI80
<b>Dimming type</b>	On/Off, 1-10V, DALI, Trailing edge
<b>Product colours</b>	Glossy White, Glossy Black
<b>Weight</b>	4.0 kg

<b>Operating temperature</b>	-20 °C to 40 °C
<b>MacAdam Ellipse</b>	3 SDCM
<b>Lifetime L90B10 (hours)</b>	> 120,000
<b>Lifetime L80B10 (hours)</b>	> 120,000
<b>Lifetime L80B50 (hours)</b>	> 120,000

**Variants (1-10V, DALI)** Compatible with EN/ IEC 60598-2-22: Suitable for emergency installations as central supply, non-maintained (Z0)

**Tuscon 2**

