


**NORTON 2** (NO-80031)**Product description**

291x291 mm

**Luminaire Structure**

- Die-cast aluminium housing with powder coating
- Die-cast aluminium heat sink with excellent thermal management
- Adjustable: Tilt 30°
- Propriety lens design for high LOR
- Remote driver (included)

**Optic****N**      **M**      **W****Product colour**

08 - Glossy White (RAL 9010)      09 - Glossy Black (HB451022M)

**NORTON 2 (NO-80031)**

**Technical information**

<b>Material</b>	Aluminium
<b>Light source</b>	4 x 12 LED
<b>Power</b>	80 W
<b>Lumen</b>	6048 - 6880 lm
<b>Efficacy</b>	76 - 86 lm/W
<b>Driver option</b>	Remote driver (included)

<b>Driver</b>	Constant current (CC)
<b>Input voltage</b>	220-240 V 50/60 Hz
<b>Optic</b>	N, M, W
<b>Optic value</b>	15°, 26°, 39°
<b>CCT / CRI</b>	3000K CRI80, 4000K CRI80
<b>Dimming type</b>	On/Off, 1-10V, DALI, Trailing edge

<b>Product colours</b>	Glossy White, Glossy Black
<b>Weight</b>	4.0 kg
<b>Operating temperature</b>	-20 °C to 50 °C
<b>Variants (1-10V, DALI)</b>	Compatible with EN/ IEC 60598-2-22: Suitable for emergency installations as central supply, non-maintained (Z0)

**Norton 2**

