


## ALDO 2 (ALD-30071) (Version 1)



### Product description


Without remote driver (CV) - Constant voltage (CV) 24 V - 37x60.6 mm - 1000 mm - RGBW




### Luminaire Structure

- Powder coated aluminium alloy housing
- Adjustable aluminium extrusion bracket for ALD-30261, ALD-30262, ALD-30263, ALD-30264, ALD-30265, ALD-30266, ALD-30271, ALD-30272, ALD-30281, ALD-30282, ALD-30291, ALD-30292, ALD-30301, ALD-30302, ALD-30801
- Adjustable galvanised steel bracket for ALD-30241, ALD-30242, ALD-30243, ALD-30244, ALD-30251, ALD-30252, ALD-30253, ALD-30254, ALD-30255, ALD-30256
- Two cable entries for through wiring
- Clear toughened glass
- Remote driver (not included)
- Uniform light distribution with uninterrupted end-to-end mounting.
- For ALD-30001 not included 24 VDC input, DMXRDM address with stable signal

### Optic



### Product colour



05 - Matt Silver  
(RAL 9006)

## ALDO 2 (ALD-30071) (Version 1)

### Technical information

|                      |                              |
|----------------------|------------------------------|
| <b>Material</b>      | Aluminium                    |
| <b>Light source</b>  | 18 LED                       |
| <b>Power</b>         | 18 W                         |
| <b>Lumen</b>         | 684 - 689 lm                 |
| <b>Efficacy</b>      | 38 lm/W                      |
| <b>Driver option</b> | Remote driver (not included) |
| <b>Driver</b>        | Constant voltage (CV)        |

|                      |                   |
|----------------------|-------------------|
| <b>Input voltage</b> | 24 VDC            |
| <b>Optic</b>         | M, W, E           |
| <b>Optic value</b>   | 30°, 45°, 25°x40° |
| <b>CCT / CRI</b>     | RGBW40            |
| <b>Bug</b>           | B1-U0-G0          |
| <b>ULR</b>           | <1%               |
| <b>ULOR</b>          | <1%               |

|                                 |                                      |
|---------------------------------|--------------------------------------|
| <b>CIE flux code n°3</b>        | 100, 98, 99                          |
| <b>Dimming type</b>             | DMX, DMX/RDM                         |
| <b>Product colours</b>          | Matt Silver                          |
| <b>Weight</b>                   | 1.7 kg                               |
| <b>Operating temperature</b>    | -20 °C to 40 °C                      |
| <b>Through wiring</b>           | Two cable entries for through wiring |
| <b>Lens / Reflector / Optic</b> | Clear toughened glass                |

**ALDO 2** (ALD-30071) (Version 1)

**Accessory**



DMX Control System  
**Control-DMX**



DMX/RDM Control System  
**Control-DMX-RDM**



Driver (CV) - On/Off - 36 W - IP67  
- 24 V  
**A34491-ND**



Driver (CV) - On/Off - 60 W - IP67  
- 24 V  
**A34591-ND**



Driver (CV) - On/Off - 100 W -  
IP67 - 24 V  
**A34791-ND**



Driver (CV) - On/Off - 150 W -  
IP67 - 24 V  
**A34891-ND**



Driver (CV) - On/Off - 200 W -  
IP67 - 24 V  
**A34991-ND**



Driver (CV) - On/Off - 350 W -  
IP67 - 24 V  
**A35091-ND**