



ROCKY 1 (RC-80011)**Product description**

118x118 mm

**Luminaire Structure**

- Die-cast aluminium housing with powder coating
- Die-cast aluminium heat sink with excellent thermal management
- Adjustable: Tilt 30°
- Proprietary lens design for high LOR
- Remote driver (included)

Optic

N

M

W

Product colour08 - Glossy White
(RAL 9010)09 - Glossy Black
(HB451022M)

ROCKY 1 (RC-80011)


Technical information

Material	Aluminium
Light source	7 LED
Power	12 W
Lumen	883 - 1040 lm
Efficacy	74 - 87 lm/W
Driver option	Remote driver (included)
Driver	Constant current (CC)

Input voltage	220-240 V 50/60 Hz
Optic	N, M, W
Optic value	15°, 26°, 35°
CCT / CRI	3000K CRI80, 4000K CRI80
Dimming type	On/Off, 1-10V, DALI, Trailing edge
Product colours	Glossy White, Glossy Black
Weight	0.6 kg

Operating temperature	-20 °C to 40 °C
MacAdam Ellipse	3 SDCM
Lifetime L90B10 (hours)	> 120,000
Lifetime L80B10 (hours)	> 120,000
Lifetime L80B50 (hours)	> 120,000
Variants (1-10V, DALI)	Compatible with EN/ IEC 60598-2-22: Suitable for emergency installations as central supply, non-maintained (Z0)

RC-80011



ROCKY 1 (RC-80011)

Accessory



DALI Control System
Control-DALI
