



**VIENNA 1** (VIE-80002)**Product description**

600x600 mm

**Luminaire Structure**

- Formed sheet steel body with powder coating
- White painted metal sheet
- UV & flame resistant, chemical & salt stable PVC
- Stainless steel fasteners in grade 304 with zinc flake coating (ZFC)
- PMMA diffuser with Opal (UGR <19) and micro prismatic (UGR <13) options for better glare control
- Integral control gear
- Recessed and surface mounted options
- Accessories: Aluminium frame for surface installation & Aluminium frame for recessed installation of fitting into gypsum plasterboard

**Optic**

O P

**Product colour**

03 - White (RAL 9003)

**VIENNA 1 (VIE-80002)**


**Technical information**

<b>Material</b>	Aluminium
<b>Light source</b>	2 x 91 LED
<b>Power</b>	35 W
<b>Lumen</b>	4300 - 4400 lm
<b>Efficacy</b>	123 - 126 lm/W
<b>Driver option</b>	Integral control gear

<b>Driver</b>	Constant current (CC)
<b>Input voltage</b>	220-240 V 50/60 Hz
<b>Optic</b>	O, P
<b>Optic value</b>	Opal, Micro-prismatic
<b>CCT / CRI</b>	3000K CRI90, 4000K CRI90
<b>Dimming type</b>	On/Off, DALI

<b>Product colours</b>	White
<b>Weight</b>	5.0 kg
<b>Operating temperature</b>	-20 °C to 40 °C
<b>Variants (DALI)</b>	Compatible with EN/ IEC 60598-2-22: Suitable for emergency installations as central supply, non-maintained (Z0)

VIE-80002



**VIENNA 1 (VIE-80002)****Accessory**

---



---

Frame for recessed installation  
of fittings into gypsum  
plasterboard ceiling SQUARE  
(White)  
**A83081**

---



---

Frame for surface installation  
SQUARE (White)  
**A83281**

---



---

Wireless bluetooth converter  
**A90291**

---



---

Xpress wireless switch  
**A90591**

---



---

DALI Control System  
**Control-DALI**

---