

PATCHI 2 (PAT-30031) (Version 1)**Product description**

Without remote driver - Constant voltage (CV) 24 V -
RGBW dynamic programming - 32
addresses/channels - 28x42.9 mm - 1000 mm

**Luminaire Structure**

- Aluminium anodised housing
- Spring snap-on mounting bracket, easy installing and aiming
- Two cable entries for through wiring
- Stainless steel fasteners in grade 304 with zinc flake coating (ZFC)
- Opal PMMA curved diffuser
- Remote driver (not included)
- Uniform light distribution with uninterrupted end-to-end mounting.
- $\geq 90^\circ$ viewing angle
- 24 VDC input, DMX512 address with stable signal

Optic

EW

Product colour05 - Matt Silver
(RAL 9006)

PATCHI 2 (PAT-30031) (Version 1)

Technical information

Material	Aluminium	Driver	Constant voltage (CV)	Product colours	Matt Silver
Light source	48 LED	Input voltage	24 VDC	Weight	0.6 kg
Power	13 W	Optic	EW	Operating temperature	-20 °C to 40 °C
Lumen	195 - 198 lm	Optic value	115°	Through wiring	Two cable entries for through wiring
Efficacy	15 lm/W	CCT / CRI	RGBW30, RGBW40	Lens / Reflector / Optic	Opal PMMA curved diffuser
Driver option	Remote driver (not included)	Dimming type	DMX		

PAT-30031



PATCHI 2 (PAT-30031) (Version 1)

Accessory



DMX Control System
Control-DMX



Driver (CV) - On/Off - 36 W - IP67
- 24 V
A34491-ND



Driver (CV) - On/Off - 60 W - IP67
- 24 V
A34591-ND



Driver (CV) - On/Off - 100 W -
IP67 - 24 V
A34791-ND



Driver (CV) - On/Off - 150 W -
IP67 - 24 V
A34891-ND



Driver (CV) - On/Off - 200 W -
IP67 - 24 V
A34991-ND



Driver (CV) - On/Off - 350 W -
IP67 - 24 V
A35091-ND