


**CEDAR 1 (CD-80001)****Product description**

118x238 mm

**Luminaire Structure**

- Die-cast aluminium housing with powder coating
- Die-cast aluminium heat sink with excellent thermal management
- Adjustable: Tilt 30°
- High-efficiency PMMA lens
- Remote driver (included)

**Optic****Product colour**

**CEDAR 1 (CD-80001)**


**Technical information**

<b>Material</b>	Aluminium
<b>Light source</b>	2 x 5 LED
<b>Power</b>	19 W
<b>Lumen</b>	1660 - 1988 lm
<b>Efficacy</b>	87 - 105 lm/W
<b>Driver option</b>	Remote driver (included)
<b>Driver</b>	Constant current (CC)
<b>Input voltage</b>	220-240 V 50/60 Hz
<b>Optic</b>	N, M, W

<b>Optic value</b>	19°, 31°, 48°
<b>CCT / CRI</b>	3000K CRI80, 4000K CRI80
<b>Bug</b>	B1-U0-G0
<b>ULR</b>	0%, <1%
<b>ULOR</b>	0%, <1%
<b>CIE flux code n°3</b>	100
<b>Dimming type</b>	On/Off, 1-10V, DALI, Trailing edge
<b>Product colours</b>	Glossy White, Glossy Black
<b>Weight</b>	1.0 kg

<b>Operating temperature</b>	-20 °C to 50 °C
<b>Lens / Reflector / Optic</b>	High-efficiency PMMA lens
<b>MacAdam Ellipse</b>	3 SDCM
<b>Lifetime L90B10 (hours)</b>	> 120,000
<b>Lifetime L80B10 (hours)</b>	> 120,000
<b>Lifetime L80B50 (hours)</b>	> 120,000
<b>Variants (On/Off, 1-10V, DALI)</b>	Compatible with EN/ IEC 60598-2-22: Suitable for emergency installations as central supply, non-maintained (Z0)

**CD-80001**



**CEDAR 1 (CD-80001)**

**Accessory**

---



DALI Control System  
**Control-DALI**

---