


HARRIER 2 (HA-60197-S)**Product description**

Integral control gear - With recessing box - Square -
Stainless steel frame

**Luminaire Structure**

- Die-cast aluminium housing
- Pre-treated before powder coating ensuring high corrosion resistance
- 6 mm thick front ring in grade 316 stainless steel or aluminium
- Single cable entry, through wiring upon request
- One cable gland supplied with 1 m of 3x1.0 sqmm outdoor cable
- Stainless steel fasteners in grade 316
- Durable silicone rubber gasket
- Clear toughened glass
- High-efficiency PMMA lens
- Integral control gear
- Recessing box in high-density polyethylene is included
- Suitable for walk-over with a maximum load of 200 kg

Optic**Product colour**

HARRIER 2 (HA-60197-S)


Technical information

| | |
|----------------------|-----------------------|
| Material | Stainless Steel |
| Light source | MR16-GU10 |
| Power | 8 W |
| Lumen | 260 - 402 lm |
| Efficacy | 35 - 54 lm/W |
| Driver option | Integral control gear |
| Driver | Constant current (CC) |

| | |
|----------------------|--------------------------|
| Input voltage | 220-240 V 50/60 Hz |
| Optic | N, M, VW, E |
| Optic value | 13°, 22°, 58°, 12°x50° |
| CCT / CRI | 3000K CRI95, 4000K CRI95 |
| Bug | B0-U3-G0 |
| ULR | 100% |
| ULOR | 100% |

| | |
|---------------------------------|---|
| Dimming type | On/Off |
| Product colours | Stainless Steel |
| Weight | 0.7 kg |
| Operating temperature | -20 °C to 50 °C |
| Cable | One cable gland supplied with 1 m of 3x1.0 sqmm outdoor cable |
| Through wiring | Single cable entry, through wiring upon request |
| Lens / Reflector / Optic | Clear toughened glass, High-efficiency PMMA lens |

HA-60197-S



HARRIER 2 (HA-60197-S)**Accessory**



Connector IP68 3 Pin Power
A62591



Connector IP68 5 Pin Power +
Signal
A613191
