


NYBRO 10 (NYB-90366)



Product description

Down - 60x95 mm - 2906 mm -RGBW DMX



microPrim™


Luminaire Structure

- Die-cast aluminium end-caps and extruded aluminium profile with powder coating
- Passive thermal management
- Single cable entry
- Stainless steel fasteners in grade 304 with zinc flake coating (ZFC)
- Durable silicone rubber gasket

- PMMA diffuser with Opal (UGR <19) and micro prismatic (UGR <13) options for better glare control
- Integral control gear
- Stainless steel brackets and screws for mounting
- Up and down light distribution options
- Wireless control available through Bluetooth connection

- Daylight and occupancy sensor options
- Emergency module (1 or 3 hours) is available upon request with 3 options (BASIC, SELF-TEST, PRO-DALI)
- Track can be integrated into NYBRO products upon request and upon receipt of design drawings


Optic



Product colour



Special finishes upon request




NYBRO 10 (NYB-90366)

Technical information

Material	Aluminium	Driver	Constant current (CC)	ULOR	52%, 60%
Light source	480 & 464 LED	Input voltage	220-240 V 50/60 Hz	Dimming type	DMX, DMX/RDM
Power	206 W	Optic	O, P	Product colours	Black, White, Matt Silver, Concrete - Urban, Softscape - Urban, Stone - Urban, Corten - Urban, Oak - Woodland, Walnut - Woodland, Pine - Woodland
Lumen	42834 lm	CCT / CRI	RGBW40		
Efficacy	680 lm/W	Bug	B1-U5-G0, B1-U5-G1		
Driver option	Integral control gear	ULR	52%, 60%	Weight	10.9 kg
				Operating temperature	-20 °C to 40 °C
				Variants (DMX/RDM)	Compatible with EN/ IEC 60598-2-22: Suitable for emergency installations as central supply, non-maintained (Z0)

NYB-90366



NYBRO 10 (NYB-90366)**Accessory**

Supply cable surface mounting
box
A80981



Continuous-coupler bracket
(60/70 mm Down & 60 mm
Down & Up profile)
A81581



Integrated track - 3 phase - DALI
for NYBRO
A81491



Integrated track - 3 phase - On-
off for NYBRO
A81391



DMX Control System
Control-DMX



DMX/RDM Control System
Control-DMX-RDM