


CEDAR 2 (CD-80031)



Product description


147x291 mm




Luminaire Structure

- Die-cast aluminium housing with powder coating
- Die-cast aluminium heat sink with excellent thermal management
- Adjustable: Tilt 30°
- High-efficiency PMMA lens
- Remote driver (included)

Optic



Product colour



CEDAR 2 (CD-80031)


Technical information

Material	Aluminium
Light source	2 x 12 LED
Power	40 W
Lumen	4004 - 4452 lm
Efficacy	100 - 111 lm/W
Driver option	Remote driver (included)
Driver	Constant current (CC)
Input voltage	220-240 V 50/60 Hz
Optic	N, M, W

Optic value	15°, 26°, 39°
CCT / CRI	3000K CRI80, 4000K CRI80
Bug	B2-U0-G0, B3-U0-G0
ULR	<1%
ULOR	<1%
CIE flux code n°3	100, 99
Dimming type	On/Off, 1-10V, DALI, Trailing edge
Product colours	Glossy White, Glossy Black
Weight	2.0 kg

Operating temperature	-20 °C to 50 °C
Lens / Reflector / Optic	High-efficiency PMMA lens
MacAdam Ellipse	3 SDCM
Lifetime L90B10 (hours)	> 120,000
Lifetime L80B10 (hours)	> 120,000
Lifetime L80B50 (hours)	> 120,000
Variants (1-10V, DALI)	Compatible with EN/ IEC 60598-2-22: Suitable for emergency installations as central supply, non-maintained (Z0)

CD-80031



CEDAR 2 (CD-80031)

Accessory



DALI Control System
Control-DALI
