


ROY 3 (RY-80101)**Product description**

4 Busbar 3 Circuit

**Luminaire Structure**

- Die-cast aluminium housing with powder coating
- Die-cast aluminium heat sink with excellent thermal management
- Adjustable: Tilt 90°, Rotation 355°
- Proprietary lens design for high LOR
- Integral control gear
- Universal adaptor compatible with any track

Optic**Product colour**

ROY 3 (RY-80101)

Technical information

Material	Aluminium
Light source	9 LED
Power	15 W
Lumen	1050 - 1272 lm
Efficacy	70 - 85 lm/W
Driver option	Integral control gear
Driver	Constant current (CC)
Input voltage	220-240 V 50/60 Hz

Optic	N, M, W
Optic value	14°, 25°, 40°
CCT / CRI	3000K, 4000K
Bug	B2-U0-G0
ULR	<1%
ULOR	<1%
CIE flux code n°3	100, 99
Dimming type	On/Off

Product colours	Glossy White, Glossy Black
Weight	0.9 kg
Operating temperature	-20 °C to 40 °C
MacAdam Ellipse	3 SDCM
Lifetime L90B10 (hours)	> 120,000
Lifetime L80B10 (hours)	> 120,000
Lifetime L80B50 (hours)	> 120,000

Variants (On/Off) Compatible with EN/ IEC 60598-2-22: Suitable for emergency installations as central supply, non-maintained (Z0)

RY-80101

