

MALMO 3 (MAL-80245)



Product description

Down - 980 mm - RGBW DMX



microPrim™


Luminaire Structure

- Extruded aluminium bended profile with powder coating
- Passive thermal management
- Multiple diameters available
- Stainless steel fasteners in grade 304 with zinc flake coating (ZFC)

- PMMA diffuser with Opal (UGR <19) and micro prismatic (UGR <13) options for better glare control
- Integral control gear
- Down light distribution only
- Wireless control available through Bluetooth connection

- Emergency module (1 or 3 hours) is available upon request with 3 options (BASIC, SELF-TEST, PRO-DALI)

Optic



Product colour



Special finishes upon request



MALMO 3 (MAL-80245)


Technical information


Material	Aluminium
Light source	7488 LED
Power	234 W
Lumen	7077 lm
Efficacy	31 lm/W
Driver option	Integral control gear

Driver	Constant current (CC)
Input voltage	220-240 V 50/60 Hz
Optic	O, P
Optic value	107°, 94°
CCT / CRI	RGBW40
Dimming type	DMX, DMX/RDM


Product colours	Black, White, Matt Silver, Concrete - Urban, Softscape - Urban, Stone - Urban, Corten - Urban, Oak - Woodland, Walnut - Woodland, Pine - Woodland
Weight	13.8 kg
Operating temperature	-20 °C to 40 °C
Variants (DMX/RDM)	Compatible with EN/ IEC 60598-2-22: Suitable for emergency installations as central supply, non-maintained (Z0)

MAL-80245




MALMO 3 (MAL-80245)**Accessory**

Decorative pattern - Type A for
MALMO 300 mm
A90821



Decorative pattern - Type C for
MALMO 300 mm
A93621



Decorative pattern - Type B for
MALMO 300 mm
A92221



DMX Control System
Control-DMX



DMX/RDM Control System
Control-DMX-RDM