

BILLUND 4 (BIU-90007)



Product description


Small - with CLO & Night dimming




Luminaire Structure

- Die-cast aluminium housing
- Pre-treated before powder coating ensuring high corrosion resistance
- Thermal heat dissipation body
- Single cable entry
- One IP68 connector supplied with 0.3 m of 3x1.0 sqmm outdoor cable
- Stainless steel fasteners in grade 304 with zinc flake coating (ZFC)
- Durable silicone rubber gasket
- Clear toughened glass
- High-efficiency polycarbonate lens
- Integral control gear
- Surge protection 10kV
- Constant lumen output (CLO) and Night-time dimming options


Optic



Product colour



Special finishes upon request




BILLUND 4 (BIU-90007)

Technical information

Material	Aluminium	Optic	M, W, T1, T2, T3, T4, T5, ME	Product colours	Black, Dark Grey, White, Matt Silver, Bronze, Concrete - Urban, Softscape - Urban, Stone - Urban, Corten - Urban, Oak - Woodland, Walnut - Woodland, Pine - Woodland
Light source	24 LED	Optic value	24°, 50°, 146°x66°, 142°x47°, 141°x59°, 100°x78°, 105°, 136°x32°	Weight	6.1 kg
Power	37 W	CCT / CRI	2700K CRI80, 3000K CRI80, 4000K CRI80	Operating temperature	-20 °C to 40 °C
Lumen	3627 - 4617 lm	Bug	B1-U0-G1, B2-U0-G0, B2-U0-G2, B3-U0-G0, B3-U0-G1	EPA (m2)	0.040
Efficacy	98 - 125 lm/W	ULR	<1%	Cable	One IP68 connector supplied with 0.3 m of 3x1.0 sqmm outdoor cable
Driver option	Integral control gear	ULOR	<1%	Through wiring	Single cable entry
Driver	Constant current (CC)	CIE flux code n°3	96, 97, 98, 99	Lens / Reflector / Optic	Clear toughened glass, High-efficiency polycarbonate lens
Input voltage	220-240 V 50/60 Hz	Dimming type	On/Off, 1-10V, DALI, CLO with DALI, CLO with Night dimming 1, CLO with Night dimming 2	Variants (On/Off, 1-10V)	Compatible with EN/ IEC 60598-2-22: Suitable for emergency installations as central supply, non-maintained (Z0)

BIU-90007



Accessory



DALI Control System
Control-DALI
