

**LIGHTALK 11** (LA-60021) (Version 1)



**Product description**


Without remote driver - With recessing box - Constant voltage (CV) 24 V - 455 mm - Class III



**Luminaire Structure**

- Die-cast aluminium end-caps
- Extruded aluminium housing
- Pre-treated before powder coating ensuring high corrosion resistance
- Stainless steel frame on request
- Two cable entries for through wiring
- Two IP67 connectors supplied with 2x0.2 m of 2x1.0 sqmm outdoor cable
- Stainless steel fasteners in grade 316
- Durable silicone rubber gasket
- Clear toughened glass
- Remote driver (not included)
- Recessing box is included
- Suitable for walk-over with a maximum load of 500 kg
- 24 VDC input, DMX/RDM address with stable signal

**Optic**



E

**Product colour**




00 - Stainless Steel

**LIGHTALK 11** (LA-60021) (Version 1)

**Technical information**

<b>Material</b>	Stainless Steel	<b>Input voltage</b>	24 VDC	<b>Dimming type</b>	On/Off
<b>Light source</b>	12 LED	<b>Optic</b>	VN, N, M, W, E	<b>Product colours</b>	Stainless Steel
<b>Power</b>	16 W	<b>Optic value</b>	13°, 15°, 26°, 43°, 20° x 35°	<b>Weight</b>	2.4 kg
<b>Lumen</b>	1401 - 1823 lm	<b>CCT / CRI</b>	3000K CRI80, 4000K CRI80	<b>Operating temperature</b>	-20 °C to 40 °C
<b>Efficacy</b>	88 - 114 lm/W	<b>Bug</b>	B2-U1-G0, B3-U1-G0	<b>Cable</b>	Two IP67 connectors supplied with 2x0.2 m of 2x1.0 sqmm outdoor cable
<b>Driver option</b>	Remote driver (not included)	<b>ULR</b>	100%	<b>Through wiring</b>	Two cable entries for through wiring
<b>Driver</b>	Constant voltage (CV)	<b>ULOR</b>	100%	<b>Lens / Reflector / Optic</b>	Clear toughened glass

LA-60021




**LIGHTALK 11 (LA-60021) (Version 1)**

**Accessory**




Cable - Connector IP67 Female 2  
Pin Power - 1000 mm  
**A65491-001**



Cable - Connector IP67 Female 2  
Pin Power - 5000 mm  
**A65491-005**



Cable - Connector IP67 Female +  
Male 2 Pin Power - 1000 mm  
**A65591-001**



Cable - Connector IP67 Female +  
Male 2 Pin Power - 5000 mm  
**A65591-005**



Connector IP67 Female 2 Pin  
Power  
**A68191**



Connector IP67 Male 2 Pin  
Power  
**A68291**



Driver (CV) - On/Off - 36 W - IP67  
- 24 V  
**A34491-ND**



Driver (CV) - On/Off - 60 W - IP67  
- 24 V  
**A34591-ND**



Driver (CV) - On/Off - 100 W -  
IP67 - 24 V  
**A34791-ND**



Driver (CV) - On/Off - 150 W -  
IP67 - 24 V  
**A34891-ND**



Driver (CV) - On/Off - 200 W -  
IP67 - 24 V  
**A34991-ND**



Driver (CV) - On/Off - 350 W -  
IP67 - 24 V  
**A35091-ND**