

**LADOR 40 (LD-20071)**



**Product description**

Supplied with specific 8 m square, straight galvanised steel pole: SPC180125-LD - RGBW




microPrim™

**Luminaire Structure**

- Die-cast aluminium housing
- Pre-treated before powder coating ensuring high corrosion resistance
- Thermal heat dissipation body
- Single cable entry, through wiring upon request
- One cable gland supplied with 2 m of 5x1.5 sqmm outdoor cable
- Stainless steel fasteners in grade 304 with zinc flake coating (ZFC)
- Durable silicone rubber gasket
- High-efficiency PMMA lens
- Clear toughened glass
- Integral control gear
- Maximum wind load resistance is 140 km/h
- Surge protection 10kV

**Optic**



**Product colour**



**Special finishes upon request**




**LADOR 40 (LD-20071)**

**Technical information**

<b>Material</b>	Aluminium
<b>Light source</b>	4 x 8 LED
<b>Power</b>	88 W
<b>Lumen</b>	3412 - 4532 lm
<b>Efficacy</b>	39 - 52 lm/W
<b>Driver option</b>	Integral control gear
<b>Driver</b>	Constant current (CC)
<b>Input voltage</b>	220-240 V 50/60 Hz
<b>Optic</b>	N, M, W, VW, E

<b>Optic value</b>	8°, 17°, 26°, 65°, 43°x11°
<b>CCT / CRI</b>	RGBW30, RGBW40
<b>ULR</b>	<1%
<b>ULOR</b>	<1%
<b>Dimming type</b>	DMX, DMX/RDM
<b>Product colours</b>	Black, Dark Grey, White, Matt Silver, Bronze, Concrete - Urban, Softscape - Urban, Stone - Urban, Corten - Urban, Oak - Woodland, Walnut - Woodland, Pine - Woodland
<b>Weight</b>	126.4 kg
<b>Operating temperature</b>	-20 °C to 40 °C
<b>EPA (m2)</b>	1.146

<b>Cable</b>	One cable gland supplied with 2 m of 5x1.5 sqmm outdoor cable
<b>Through wiring</b>	Single cable entry, through wiring upon request
<b>Lens / Reflector / Optic</b>	High-efficiency PMMA lens, Clear toughened glass
<b>MacAdam Ellipse</b>	7 SDCM
<b>Lifetime L90B10 (hours)</b>	> 50,000
<b>Lifetime L80B10 (hours)</b>	> 68,000
<b>Lifetime L80B50 (hours)</b>	> 100,000
<b>Variants (DMX/RDM)</b>	Compatible with EN/ IEC 60598-2-22: Suitable for emergency installations as central supply, non-maintained (Z0)



**LADOR 40 (LD-20071)****Accessory**


DMX Control System  
**Control-DMX**



DMX/RDM Control System  
**Control-DMX-RDM**



Linear spread lens  
**A51314**



Honeycomb louvre  
**A52021**



Anti-glare visor  
**A53031**

Please contact the factory for technical details if you wish to use Anti-glare accessories, Colour filters, Lenses and slip glasses in combination.

**Pole (required)**

8 m - Square, straight galvanised  
steel pole for LADOR  
**SPC180125-LD**