




**ALDO 3** (ALD-30161) (Version 1)**Product description**

Without remote driver (CV) - Constant voltage (CV) 24 V - 47x72 mm - 500 mm

**Luminaire Structure**

- Powder coated aluminium alloy housing
- Adjustable aluminium extrusion bracket for ALD-30261, ALD-30262, ALD-30263, ALD-30264, ALD-30265, ALD-30266, ALD-30271, ALD-30272, ALD-30281, ALD-30282, ALD-30291, ALD-30292, ALD-30301, ALD-30302, ALD-30801
- Adjustable galvanised steel bracket for ALD-30241, ALD-30242, ALD-30243, ALD-30244, ALD-30251, ALD-30252, ALD-30253, ALD-30254, ALD-30255, ALD-30256
- Two cable entries for through wiring
- Clear toughened glass
- Remote driver (not included)
- Uniform light distribution with uninterrupted end-to-end mounting.
- For ALD-30001 not included 24 VDC input, DMXRDM address with stable signal

**Optic****Product colour**

05 - Matt Silver  
(RAL 9006)

**ALDO 3** (ALD-30161) (Version 1)

**Technical information**

|                      |                              |                      |                          |                                 |                                      |
|----------------------|------------------------------|----------------------|--------------------------|---------------------------------|--------------------------------------|
| <b>Material</b>      | Aluminium                    | <b>Driver</b>        | Constant voltage (CV)    | <b>Product colours</b>          | Matt Silver                          |
| <b>Light source</b>  | 12 LED                       | <b>Input voltage</b> | 24 VDC                   | <b>Weight</b>                   | 0.9 kg                               |
| <b>Power</b>         | 24 W                         | <b>Optic</b>         | N, M, W, E               | <b>Operating temperature</b>    | -20 °C to 40 °C                      |
| <b>Lumen</b>         | 1483 - 1607 lm               | <b>Optic value</b>   | 12°, 30°, 45°, 15°x50°   | <b>Through wiring</b>           | Two cable entries for through wiring |
| <b>Efficacy</b>      | 62 - 67 lm/W                 | <b>CCT / CRI</b>     | 3000K CRI80, 4000K CRI80 | <b>Lens / Reflector / Optic</b> | Clear toughened glass                |
| <b>Driver option</b> | Remote driver (not included) | <b>Dimming type</b>  | On/Off                   |                                 |                                      |

**ALDO 3** (ALD-30161) (Version 1)**Accessory**

---



---

Driver (CV) - On/Off - 36 W - IP67  
- 24 V  
**A34491-ND**

---



---

Driver (CV) - On/Off - 60 W - IP67  
- 24 V  
**A34591-ND**

---



---

Driver (CV) - On/Off - 100 W -  
IP67 - 24 V  
**A34791-ND**

---



---

Driver (CV) - On/Off - 150 W -  
IP67 - 24 V  
**A34891-ND**

---



---

Driver (CV) - On/Off - 200 W -  
IP67 - 24 V  
**A34991-ND**

---



---

Driver (CV) - On/Off - 350 W -  
IP67 - 24 V  
**A35091-ND**

---