

MARVEL 1 (MAV-20001)



Product description

Ø70 mm - Supplied with specific 2.5 m cylindrical, straight aluminium pole: APD125070-MARVEL - Optic 90°



microPrim™

Luminaire Structure

- Die-cast aluminium housing
- Extruded aluminium column
- Pre-treated before powder coating ensuring high corrosion resistance
- Single cable entry
- One IP68 connector supplied with 0.2 m of 3x1.0 sqmm outdoor cable
- Stainless steel fasteners in grade 304 with zinc flake coating (ZFC)
- Durable silicone rubber gasket
- High-efficiency PMMA lens
- Clear toughened glass
- Integral control gear

Optic




G

Product colour



Special finishes upon request



MARVEL 1 (MAV-20001)

Technical information

Material	Aluminium
Light source	6 LED
Power	11 W
Lumen	1096 - 1153 lm
Efficacy	100 - 105 lm/W
Driver option	Integral control gear
Driver	Constant current (CC)
Input voltage	220-240 V 50/60 Hz

Optic	G
Optic value	120°X 92°
CCT / CRI	3000K CRI80, 4000K CRI80
Bug	B1-U1-G0
ULR	1%
ULOR	1%
CIE flux code n°3	98
Dimming type	On/Off, DALI

Product colours	Black, Dark Grey, White, Matt Silver, Bronze, Concrete - Urban, Softscape - Urban, Stone - Urban, Corten - Urban, Oak - Woodland, Walnut - Woodland, Pine - Woodland
Weight	8.0 kg
Operating temperature	-20 °C to 40 °C
EPA (m2)	0.212
Cable	One IP68 connector supplied with 0.2 m of 3x1.0 sqmm outdoor cable
Through wiring	Single cable entry
Lens / Reflector / Optic	High-efficiency PMMA lens, Clear toughened glass
Variants (DALI)	Compatible with EN/ IEC 60598-2-22: Suitable for emergency installations as central supply, non-maintained (Z0)



MARVEL 1 (MAV-20001)**Accessory**



Root mount kit
A24391

Pole (required)



2.5 m - Cylindrical, straight
aluminium pole for MARVEL
APD125070-MARVEL
