

PATCHI 1 (PAT-30001) (Version 1)**Product description**


Without remote driver - Constant voltage (CV) 24 V -
RGBW dynamic programming - 16
addresses/channels - 43.4x57.8 mm - 500 mm

**Luminaire Structure**

- Aluminium anodised housing
- Spring snap-on mounting bracket, easy installing and aiming
- Two cable entries for through wiring
- Stainless steel fasteners in grade 304 with zinc flake coating (ZFC)
- Opal PMMA curved diffuser
- Remote driver (not included)
- Uniform light distribution with uninterrupted end-to-end mounting.
- $\geq 90^\circ$ viewing angle
- 24 VDC input, DMX512 address with stable signal

Optic

EW

Product colour05 - Matt Silver
(RAL 9006)

PATCHI 1 (PAT-30001) (Version 1)


Technical information

Material	Aluminium
Light source	24 LED
Power	6 W
Lumen	21 lm
Efficacy	4 lm/W
Driver option	Remote driver (not included)

Driver	Constant voltage (CV)
Input voltage	24 VDC
Optic	EW
Optic value	90°
CCT / CRI	RGBW40
Dimming type	DMX

Product colours	Matt Silver
Weight	0.4 kg
Operating temperature	-20 °C to 40 °C
Through wiring	Two cable entries for through wiring
Lens / Reflector / Optic	Opal PMMA curved diffuser

PAT-30001



PATCHI 1 (PAT-30001) (Version 1)**Accessory**

DMX Control System
Control-DMX



Driver (CV) - On/Off - 36 W - IP67
- 24 V
A34491-ND



Driver (CV) - On/Off - 60 W - IP67
- 24 V
A34591-ND



Driver (CV) - On/Off - 100 W -
IP67 - 24 V
A34791-ND



Driver (CV) - On/Off - 150 W -
IP67 - 24 V
A34891-ND



Driver (CV) - On/Off - 200 W -
IP67 - 24 V
A34991-ND



Driver (CV) - On/Off - 350 W -
IP67 - 24 V
A35091-ND