



SIDNEY 1 (SI-80001)**Product description**

Ø87 mm

**Luminaire Structure**

- Die-cast aluminium housing with powder coating
- Die-cast aluminium heat sink with excellent thermal management
- Aluminium reflector with white powder coating
- Remote driver (included)

Optic**N** **M** **W****Product colour**

08 - Glossy White (RAL 9010) 09 - Glossy Black (HB451022M)

SIDNEY 1 (SI-80001)

Technical information

Material	Aluminium
Light source	3 LED
Power	6 W
Lumen	247 - 346 lm
Efficacy	41 - 58 lm/W
Driver option	Remote driver (included)
Driver	Constant current (CC)


Input voltage	220-240 V 50/60 Hz
Optic	N, M, W
Optic value	28°, 35°, 46°
CCT / CRI	3000K CRI80, 4000K CRI80
Dimming type	On/Off, 1-10V, DALI
Product colours	Glossy White, Glossy Black
Weight	0.3 kg

Operating temperature	-20 °C to 40 °C
MacAdam Ellipse	3 SDCM
Lifetime L90B10 (hours)	> 120,000
Lifetime L80B10 (hours)	> 120,000
Lifetime L80B50 (hours)	> 120,000

Variants (On/Off, 1-10V, DALI)

Compatible with EN/ IEC 60598-2-22: Suitable for emergency installations as central supply, non-maintained (Z0)

SI-80001



SIDNEY 1 (SI-80001)

Accessory



DALI Control System
Control-DALI
