



**VICTORIA 1** (VIC-80001)**Product description**

Optic arrangement type 1

**Luminaire Structure**

- Formed sheet steel body with powder coating
- White painted metal sheet
- One size: 600x600 mm
- Stainless steel fasteners in grade 304 with zinc flake coating (ZFC)
- Integral control gear
- Recessed and surface mounted options
- Accessories: Aluminium frame for surface installation & Aluminium frame for recessed installation of fitting into gypsum plasterboard

**Optic****Product colour**

03 - White (RAL 9003)

**VICTORIA 1 (VIC-80001)**


**Technical information**

<b>Material</b>	Aluminium
<b>Light source</b>	24 LED
<b>Power</b>	7 W
<b>Lumen</b>	1000 lm
<b>Efficacy</b>	143 lm/W

<b>Driver option</b>	Integral control gear
<b>Driver</b>	Constant current (CC)
<b>Input voltage</b>	220-240 V 50/60 Hz
<b>Optic</b>	W, VW
<b>Optic value</b>	60°, 90°


<b>CCT / CRI</b>	3000K CRI90, 4000K CRI90
<b>Dimming type</b>	On/Off
<b>Product colours</b>	White
<b>Weight</b>	1.9 kg
<b>Operating temperature</b>	-20 °C to 40 °C

VIC-80001



**VICTORIA 1 (VIC-80001)****Accessory**


---



---

Frame for recessed installation  
of fittings into gypsum  
plasterboard ceiling SQUARE  
(White)  
**A83081**

---



---

Frame for surface installation  
SQUARE (White)  
**A83281**

---



---

Wireless bluetooth converter  
**A90291**

---



---

Xpress wireless switch  
**A90591**

---



---

DALI Control System  
**Control-DALI**

---