



AMOS 2 (AM-80021)**Product description**

Ø138 mm

**Luminaire Structure**

- Die-cast aluminium housing with powder coating
- Die-cast aluminium heat sink with excellent thermal management
- Aluminium reflector with white powder coating
- Remote driver (included)

Optic

N M W

Product colour

08 - Glossy White (RAL 9010) 09 - Glossy Black (HB451022M)

AMOS 2 (AM-80021)

Technical information


Material	Aluminium
Light source	9 LED
Power	15 W
Lumen	1044 - 1398 lm
Efficacy	70 - 93 lm/W
Driver option	Remote driver (included)
Driver	Constant current (CC)
Input voltage	220-240 V 50/60 Hz
Optic	N, M, W

Optic value	33°, 40°, 46°
CCT / CRI	3000K CRI80, 4000K CRI80
Bug	B1-U0-G0, B1-U0-G1, B2-U0-G1
ULR	<1%
ULOR	<1%
CIE flux code n°3	98, 99
Dimming type	On/Off, 1-10V, DALI, Trailing edge
Product colours	Glossy White, Glossy Black
Weight	1.0 kg

Operating temperature	-20 °C to 40 °C
Lens / Reflector / Optic	Aluminium reflector with white powder coating
MacAdam Ellipse	3 SDCM
Lifetime L90B10 (hours)	> 120,000
Lifetime L80B10 (hours)	> 120,000
Lifetime L80B50 (hours)	> 120,000

Variants (1-10V, DALI) Compatible with EN/ IEC 60598-2-22: Suitable for emergency installations as central supply, non-maintained (Z0)

AM-80021



AMOS 2 (AM-80021)

Accessory



DALI Control System
Control-DALI
